



ULT-C2BIRM2812D

2 Megapixel/1080p TVI Outdoor Bullet, 150' IR Range, True Day & Night, IP66 Weather Resistant, Dual Voltage

Features

- 2 Megapixel (1920 x 1080) Resolution
- Motorized 2.8-12mm Lens
- True Day/Night
- True WDR 120dB
- 150' IR Range with EXIR Technology
- Up The Cable (UTC) Function
- IP66 Weather Resistant
- Withstand up to -40° Operation
- Dual Voltage

| | |
|--------------------------------|---|
| Model Number | ULT-C2BIRM2812D |
| Image Sensor | 1 / 3" Progressive Scan CMOS |
| Video Format | PAL / NTSC |
| Effective Pixels | 1920(H)*1080(V) |
| Min. Illumination | 0.01 Lux @ (F1.2,AGC ON),0 Lux with IR |
| Shutter speed | 1/25 s to 1/50,000 s |
| Lens | 2.8-12mm @ F1.4, Angle of view: 92° – 32° Motorized |
| Lens Mount | φ14 |
| Day & Night | ICR |
| Wide dynamic range | True WDR, 120 dB |
| Synchronization | Internal synchronization |
| Video Frame Rate | 1080p@30fps |
| HD Video Output | 1 Analog HD output |
| CVBS Output | 1Vp-p Composite Output(75Ω / BNC) |
| S / N Ratio | More than 52dB |
| Scene | Indoor, Outdoor, Indoor1, LOW-LIGHT |
| Camera ID | On/off (15 characters, position programmable) |
| AGC | Support |
| D/N Mode | Color/BW/EXT |
| White Balance | ATW, AWC-SET, Indoor, Outdoor, Manua |
| Privacy Mask | On/Off, maximum 8 zones |
| Motion Detection | On/Off, maximum 4 zones |
| BLC | Support |
| Anti-flicker | On/off |
| Language | English, Japanese, CHN1, CHN2, Korean, German, French, Italian, Spanish, Polish, Russian, Portuguese, Dutch, Turkish, Hebrew and Arabic |
| Function | Eclipse, Digital noise reduction, Digital zoom(62x), Slow shutter, Mirror, Defog, Defect pixel correction, SMART D-ZOOM |
| Working Temperature / Humidity | -4 °F – 140 °F (-20 °C – 60 °C) Humidity 90% or less (non-condensing) |
| Power Supply | 12 VDC, 24 VAC |
| Power Consumption | 12VDC: Max. 7W ; 24V AC: Max. 10W |
| Weather Proof Ratings | IP66 |
| IR Range | Up to 150 ft |
| Communication | Up the coax(need UTC controller) Protocol: Pelco-C(-Coaxitron) |
| Dimensions | 300.82×100.76×107.55mm(11.84"×3.97"×4.23") |
| Weight | 1.54 lbs (700 g) |

Ordering Information

ULT-C2BIRM2812D: 2 Megapixel Motorized Bullet, 2.8-12mm