





## **ULT-C2BIRM2812** 2 Megapixel/1080p TVI Outdoor Bullet, 2.8-12mm Motorized Lens, 150' IR Range, Dual Voltage

## Features

- 2 Megapixel (1920 x 1080) Resolution
- Motorized 2.8-12mm Lens
- True Day/Night
- True WDR 120dB
- 150' IR Range with EXIR Technology
- Up The Cable (UTC) Function
- IP66 Weather Resistant
- Withstand up to -40° Operation
- Dual Voltage

Model Number	ULT-C2BIRM2812
Image Sensor	1 / 3" Progressive Scan CMOS
Signal System	PAL / NTSC
Effective Pixels	1920(H)*1080(V)
Min. Illumination	0.01 Lux @ (F1.2,AGC ON),0 Lux with IR 0.014 Lux @ (F1.4,AGC ON),0 Lux with IR
Shutter Speed	1/25 s to 1/50,000s
Lens (Angle of View)	2.8-12mm @ F1.4, (92° – 32°)
Auto Iris	Yes
Lens Mount	φ14
Day & Night	IR Cut Filter with Auto Switch
Wide Dynamic Range	DWDR
Synchronization	Internal synchronization
Video Frame Rate	1080p @ 30fps
HD Video Output	1 Analog HD output
S / N Ratio	More than 52dB
Scene	Indoor, Outdoor, Indoor1, LOW-LIGHT
Camera ID	On/off (15 characters, position programmable)
AGC	Support
D/N Mode	Color/BW/EXT
White Balance	ATW, AWC-SET, Indoor, Outdoor, Manual
Privacy Mask	On/Off, maximum 2 zones
Motion Detection	On / Off, maximum 4 zones
BLC	Support
Anti-flicker	On/off
Language	English, Japanese, CHN1, CHN2, Korean, German, French, Italian, Spanish, Polish, Russian, Portuguese, Dutch, Turkish, Hebrew and Arabic
Function	Eclipse, Digital noise reduction, Digital zoom(62x), Slow shutter, Mirror, Defog, Defect pixel correction, SMART D-ZOOM
Working Temperature / Humidity	-4 °F − 140 °F (-20 °C − 60 °C)
Humidity	Humidity 90% or less (non-condensing)
Power Supply	12 VDC; 24 VAC
Power Consumption	12V DC: Max. 7W ; 24V AC: Max. 10W
Housing	IP66
IR Range	Up to 150 ft
Communication	Up the coax(need UTC controller), Protocol: Pelco-C (Coaxitron)
Dimensions	3.62 x 3.34 x 10.6 in (91.94 x 84.83 x 269.2mm)
Weight	1.59 lbs (700g)

Ordering Information

**ULT-C2BIRM2812:** 2 Megapixel Motorized Bullet, 2.8-12mm

2 MEGAPIXEL | 1080p