



ULT-C2BXIR2812 2 Megapixel/1080p TVI Outdoor Bullet, 2.8-12mm, WDR, 164' EXIR Range, Dual Voltage

Features

- 2 Megapixel (1920 x 1080) Resolution
- Varifocal 2.8-12mm Lens
- True Day/Night
- True WDR 120dB
- 164' IR Range with Smart EXIR Technology
- Up The Cable (UTC) Function
- IP66 Weather Resistant
- Analog Video Output
- Dual Voltage

| | |
|--------------------------------|---|
| Model Number | ULT-C2BXIR2812 |
| Image Sensor | 1 / 3" Progressive Scan CMOS |
| Signal System | PAL / NTSC |
| Effective Pixels | 1920(H)*1080(V) |
| Min. Illumination | 0.01 Lux @ (F1.2,AGC ON),0 Lux with IR 0.014 Lux @ (F1.4,AGC ON),0 Lux with IR |
| Shutter Speed | 1/25 s to 1/50,000s |
| Lens (Angle of View) | 2.8-12mm @ F1.4, (92° – 32°) |
| Auto Iris | Yes |
| Lens Mount | φ14 |
| Day & Night | IR Cut Filter with Auto Switch |
| Wide Dynamic Range | True WDR, 120 dB |
| Synchronization | Internal synchronization |
| Video Frame Rate | 1080p @ 30fps |
| HD Video Output | 1 Analog HD output |
| CVBS Output | 1Vp-p Composite Output(75Ω / BNC) |
| S / N Ratio | More than 52dB |
| Scene | Indoor, Outdoor, Indoor1, LOW-LIGHT |
| Camera ID | On/off (15 characters, position programmable) |
| AGC | Support |
| D/N Mode | Color/BW/EXT |
| White Balance | ATW, AWC-SET, Indoor, Outdoor, Manual |
| Privacy Mask | On/Off, maximum 8 zones |
| Motion Detection | On / Off, maximum 4 zones |
| BLC | Support |
| Anti-flicker | On/off |
| Language | English, Japanese, CHN1, CHN2, Korean, German, French, Italian, Spanish, Polish, Russian, Portuguese, Dutch, Turkish, Hebrew and Arabic |
| Function | Eclipse, Digital noise reduction, Digital zoom(62x), Slow shutter, Mirror, Defog, Defect pixel correction, SMART D-ZOOM |
| Working Temperature / Humidity | -4 °F – 140 °F (-20 °C – 60 °C) |
| Humidity | Humidity 90% or less (non-condensing) |
| Power Supply | 12 VDC; 24 VAC |
| Power Consumption | 12V DC: Max. 7W ; 24V AC: Max. 10W |
| Housing | IP66 |
| IR Range | Up to 150 ft |
| Communication | Up the coax(need UTC controller) Protocol: Pelco-C(-Coaxifron) |
| Dimensions | 11.84 × 3.97 × 4.23 in (300.82 × 100.76 × 107.55mm) |
| Weight | 1.54 lbs (700g) |

Ordering Information

ULT-C2BXIR2812: 2 Megapixel Bullet, 2.8-12mm

*To use these mounts with the selected cameras drill the holes needed into the mount using the diagram included with the camera. InVid Tech, reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.

2 MEGAPIXEL | 1080p