



ULT-C2BXIRA2812

2 Megapixel TVI, Outdoor Bullet, 2.8-12mm Auto-Focus Motorized, 120' EXIR Range, Dual Voltage, up to -40

Features

- 2 Megapixel (1920 x 1080) Resolution
- Motorized Auto-Focus 2.8-12mm Lens
- True Day/Night
- True WDR 120dB
- 120' IR Range with EXIR Technology
- Up The Cable (UTC) Function
- IP66 Weather Resistant
- Withstand up to -40° Operation
- Dual Voltage

Model Number	ULT-C2BXIRA2812
Image Sensor	2MP CMOS Sensor
Video Format	95 PAL / NTSC
Effective Pixels	1928(H)*1088(V)
Min. Illumination	0.01 Lux @ (F1.2,AGC ON),0 Lux with IR
Shutter speed	1/25 s to 1/50,000 s
Lens	2.8-12mm @ F1.2, Angle of view: 92° – 32°
Lens Mount	φ14
Day & Night	ICR
Wide dynamic range	120dB True WDR
Synchronization	Internal synchronization
Video Frame Rate	1080p@30fps
HD Video Output	1 Analog HD output
CVBS	Yes
Scene	Indoor, Outdoor, Indoor1, LOW-LIGHT
AGC	Support
D/N Mode	Color/BW/EXT
White Balance	ATW, AWC-SET, Indoor, Outdoor, Manua
BLC	Support
S/N Ratio	More than 52db
Function	Eclipse, Digital noise reduction, Digital zoom(62x), Slow shutter, Mirror, Defog, Defect pixel, correction, SMART D-ZOOM
Working Temperature / Humidity	-40 °C – 60 °C (-40 °F – 140 °F) Humidity 90% or less (non-condensing)
Power Supply	12 VDC ; -A: 12 VDC, 24 VAC
Power Consumption	12V DC: Max. 7W ; 24V AC: Max. 10W
Weather Proof Ratings	IP66
IR Range	Up to 120 ft
Communication	Up the coax(need UTC controller), Protocol: Pelco-C (Coaxitron)
Dimensions	3.62" x 3.34" x 3.34"
Weight	1.98 lbs

Ordering Information

ULT-C2BXIRA2812: 2 Megapixel Motorized Auto-Iris Bullet, 2.8-12mm, White Housing

InVid Tech, reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.