



ULT-C2BXIRM2808

2 Megapixel TVI Bullet Motorized 2.8-8mm, 131' EXIR Range, 12VDC

Features

- 2 Megapixel (1920 x 1080) Resolution
- Motorized 2.8-12mm Lens
- True Day/Night
- 131' IR Range with Smart EXIR Technology
- Up The Cable (UTC) Function
- IP66 Weather Resistant
- 12VDC Only Operation

| | |
|----------------------------|---|
| Pick-up Element | 1/ 2.7" CMOS image sensor |
| Number of Pixels | 1930(H) x 1088(V) |
| Video Frame Rate | 1080P@30fps / 1080P@25fps |
| Min. Illumination | 0.1 Lux / F1.6(Wide)~F2.8(Tele), 0 Lux (IR LED ON) |
| S/N Ratio | More than 48dB (AGC OFF) |
| Shutter Speed | 1/30 (1/25) sec ~ 1/720000 (1/600000) sec |
| Lens | motorized f2.8 ~ f8.0mm / F1.6 ~ 2.8 |
| Lens Angle | Wide: 104° (Horizontal) / 56° (Vertical) / 126° (Diagonal) Tele: 57° (Horizontal) / 32° (Vertical) / 65° (Diagonal) |
| IR LED | 4 units |
| IR Effective Distance | 131' IR Range |
| IR Shift | YES |
| Day & Night Mode | YES |
| IRIS Mode | AES |
| White Balance | AUTO / USER / PUSH / 8000K / 6000K / 4200K / 3200K |
| AGC | Adjustable |
| Sharpness | Adjustable |
| Flickerless | 50HZ / 60HZ / OFF |
| BLC | Adjustable |
| IR Brightness Adjustment | YES |
| IP Rating | IP66 |
| Operating Temperature | -25°C ~ 50°C |
| Operating Humidity | 90% or less relative humidity |
| Power Source (±10%) | DC12V / 1A |
| Current Consumption (±10%) | 220mA (IR LED OFF) / 900mA (IR LED ON) |
| Net Weight (kg) | 5.29 lbs (2.4 kg) |

Ordering Information

ULT-C2BXIRM2808: 2 Megapixel Motorized Bullet, 2.8-8mm