



ULT-C2DRIR2812DD 2 Megapixel/1080p TVI Outdoor Rugged Dome, 2.8-12mm Lens, 120' IR Range, Dual Voltage

Features

- 2 Megapixel (1920 x 1080) Resolution
- 2.8-12mm Lens
- True Day/Night
- Dual Output
- 120' IR Range
- Up The Cable (UTC) Function
- IP66 Weather Resistant
- IK10 Vandal Resistant
- -40° Operation
- Dual Voltage

Model Number	ULT-C2DRIR2812DD
Image Sensor	1 / 3" Progressive Scan CMOS
Signal System	PAL / NTSC
Effective Pixels	1930(H)*1088(V)
Min. Illumination	0.1 Lux @ (F1.2, AGC ON), 0 Lux with IR
Shutter Speed	1/25 s to 1/50,000s
Lens (Angle of View)	2.8 – 12 mm @ F1.4 Angle of View: 102° – 95°
Auto Iris	Yes
Lens Mount	Pan: 0 – 360°, Tilt: 0 – 90°, Rotation: 0 – 360°
Day & Night	IR Cut Filter with Auto Switch
Synchronization	Internal synchronization
Video Frame Rate	1080p @ 30fps
HD Video Output	1 HD-TV1 output up to 1200ft with RG59U 95%
CVBS Output	1Vp-p Composite Output(75Ω / BNC)
S / N Ratio	More than 52dB
Scene	Indoor, Outdoor, Indoor1, LOW-LIGHT
Camera ID	On/off (15 characters, position programmable)
AGC	Support
D/N Mode	Color/BW/EXT
White Balance	ATW, AWC-SET, Indoor, Outdoor, Manual
Privacy Mask	On / Off, maximum 2 zones
Motion Detection	On / Off, maximum 4 zones
BLC	Support
Anti-flicker	On/off
Language	English, Japanese, CHN1, CHN2, Korean, German, French, Italian, Spanish, Polish, Russian, Portuguese, Dutch, Turkish, Hebrew and Arabic
Function	Digital noise reduction, Digital zoom(62x)
Working Temperature / Humidity	-40 °F – 140 °F (-40 °C – 60 °C)
Humidity	Humidity 90% or less (non-condensing)
Power Supply	Dual Volt: 12 VDC, 24 VAC
Power Consumption	Max. 5W
Housing	IP66, IK10
IR Range	Up to 120 ft
Communication	OSD (UTC Control) via DVR
Dimensions	Ø5.72 x 4.9 in (145.2 x 124.4mm)
Weight	1.95lbs (884g)

Mounting Options



Ordering Information

ULT-C2DRIR2812DD: 2 Megapixel Dome, 2.8-12mm, Dual Voltage

2 MEGAPIXEL | 1080p

InVid Tech, reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.