



### ULT-C2DRIRM2812DD

2 Megapixel, TVI Outdoor Dome with Motorized 2.8-12mm Lens, 120' IR Range, Dual Voltage

#### Features

- 2 Megapixel (1920 x 1080) Resolution
- 2.8-12mm Motorized Lens
- True Day/Night
- Dual Output
- 120' IR Range
- Up The Cable (UTC) Function
- IP66 Weather Resistant
- IK10 Vandal Resistant
- -40° Operation
- Dual Voltage
- Through InVid Tech DVR: Free App, CMS & MAC Client

Model Number	ULT-C2DRIRM2812DD
Image Sensor	1 / 3" Progressive Scan CMOS
video Format	PAL / NTSC
Effective Pixels	1920(H)*1080(V)
Min. Illumination	0.01 Lux @ (F1.2,AGC ON),0 Lux with IR
Shutter speed	1/30s to 1/50,000s
Lens	2.8-12mm @ F1.4, Angle of view: 92° - 32°
Angle Adjustment	Pan: 0 - 355°, Tilt: 0 - 80°
Day & Night	ICR
Wide dynamic range	True WDR, 120 dB
Video Frame Rate	1080p@30fps
HD Video Output	1 Analog HD output
CVBS Output	1Vp-p Composite Output(75Ω / BNC)
S / N Ratio	More than 52dB
Scene	Indoor, Outdoor, Indoor1, LOW-LIGHT
Camera ID	On/off (15 characters, position programmable)
AGC	Support
D/N Mode	Color/BW/EXT
Privacy Mask	On/Off, maximum 8 zones
Motion Detection	On/Off, maximum 4 zones
BLC	Support
Anti-flicker	On/off
Working Temperature / Humidity	-4 °F - 140 °F (-20 °C - 60 °C) Humidity 90% or less (non-condensing)
Power Supply	12 VDC, 24 VAC
Power Consumption	12 VDC: Max. 4.5W ; 24 VAC: Max. 6.5W
Ratings	IP66, IK10
IR Range	Up to 120 ft
Dimensions	φ5.72" × 4.89" (φ145.3 × 124.2 mm)
Weight	1.95 lb (880 g)

#### Ordering Information

**ULT-C2DRIRM2812DD:** 2 Megapixel Dome, 2.8-12mm, Dual Voltage

**2 MEGAPIXEL | 1080p**

InVid Tech, reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.