



ULT-C2DRIRM2812 2 Megapixel/1080p TVI Outdoor Rugged Dome, 2.8-12mm Motorized Lens, 150' IR Range, Dual Voltage

Features

- 2 Megapixel (1920 x 1080) Resolution
- Motorized 2.8-12mm Lens
- True Day/Night
- True WDR 120dB
- 150' IR Range
- Up The Cable (UTC) Function
- IP66 Weather Resistant
- -40° Operation
- Dual Voltage

Model Number	ULT-C2DRIRM2812
Image Sensor	2MP CMOS Sensor
Signal System	PAL / NTSC
Effective Pixels	1928(H)*1088(V)
Min. Illumination	0.01 Lux @ (F1.2,AGC ON),0 Lux with IR
Shutter Speed	1/25 s to 1/50,000 s
Lens	2.8~12mm
Day & Night	ICR
Wide Dynamic Range	True WDR
Synchronization	Internal synchronization
Video Frame Rate	1080p@25fps/1080p@30fps
HD Video Output	1 Analog HD output
CVBS Output	Yes
S / N Ratio	More than 52dB
Scene	Indoor, Outdoor, Indoor1, LOW-LIGHT
Camera ID	On/off (15 characters, position programmable)
AGC	Support
D/N Mode	Color/BW/EXT
White Balance	ATW, AWC-SET, Indoor, Outdoor, Manual
Privacy Mask	On/Off, maximum 2 zones
Motion Detection	On/Off, maximum 4 zones
BLC	Support
Anti-flicker	On/off
Language	English, Japanese, CHN1, CHN2, Korean, German, French, Italian, Spanish, Polish, Russian, Portuguese, Dutch, Turkish, Hebrew and Arabic
Scene	Indoor, Outdoor, Indoor1, LOW-LIGHT
Function	Eclipse, Digital noise reduction, Digital zoom(62x), Slow shutter, Mirror, Defog, Defect pixel correction, SMART D-ZOOM
Working Temperature / Humidity	-40 °C – 60 °C (-40 °F – 140 °F) Humidity 90% or less (non-condensing)
Power Supply	12 VDC ;24 VAC
Power Consumption	12V DC: Max. 4.5W, 24V AC: Max. 6.5W
Housing	IP66, IK10
IR Range	Up to 120 ft
Communication	Up the coax(need UTC controller) Protocol: Pelco-C(-Coaxitron)
Dimensions	φ145.3 × 124.2 mm (φ5.72" × 4.89")
Weight	3.53 lbs

Ordering Information

- ULT-C2DRIRM2812:** 2 Megapixel Motorized Dome, 2.8-12mm
ULT-C2DRIRM2812B: 2 Megapixel Motorized Dome, 2.8-12mm, Black

2 MEGAPIXEL | 1080p