



ULT-C2DRIRN

2 Megapixel TVI, Outdoor Dome, 2.8mm, 65' EXIR Range, up to -40, WDR, 12VDC, White Housing

Features

- Fixed Lens
- 2 Megapixel (1920 x 1080) Resolution
- 12VDC Only Operation
- True Day/Night
- True WDR 120dB
- Withstand up to -40° Operation
- IP67 Weather Resistant
- Up The Cable (UTC) Function
- 65' IR Range with EXIR Technology
- Through InVid Tech DVR: Free App, CMS & MAC Client

| | |
|----------------------------------|--|
| Model Number | ULT-C2DRIRN |
| Image Sensor | 2.0 megapixel progressive scan CMOS |
| Signal System | PAL/NTSC |
| Frame Rate | PAL: 1080p@25fps, NTSC: 1080p@30fps |
| Resolution | 1920 (H) × 1080 (V) |
| Min. illumination | Color: 0.005 Lux @ (F2.0, AGC ON), 0 Lux with IR |
| Shutter Time | PAL: 1/25 s to 1/50, 000 s, NTSC: 1/30 s to 1/50, 000 s |
| Slow Shutter | Max.: 16 times |
| Lens | 2.8 mm, 3.6 mm, 6 mm fixed focal lens |
| Horizontal Field of View | 103.5° (2.8 mm), 82.6° (3.6 mm), 54.4° (6 mm) |
| Lens Mount | M12 |
| Day & Night | IR cut filter |
| Angle Adjustment | Pan: 0° to 360°, Tilt: 0° to 75°, Rotate: 0° to 360° |
| Synchronization | Internal synchronization |
| WDR (Wide Dynamic Range) | > 120 dB |
| Menu | |
| AGC | Support |
| Day/Night Mode | Auto/Color/BW (Black and White) |
| White Balance | ATW/MANUAL |
| Privacy Mask | ON/OFF, 4 programmable privacy masks |
| Motion Detection | 4 programmable motion areas |
| Backlight Compensation | WDR/BLC/HLC/OFF |
| 3D DNR (Digital Noise Reduction) | On |
| Language | English, Chinese |
| Functions | Brightness, Sharpness, Mirror, Smart IR |
| Interface | |
| Video Output | 1 HD analog output |
| General | |
| Operating Conditions | -40 °F to 140 °F (-40 °C to 60 °C), humidity: 90% or less (non-condensation) |
| Power Supply | 12 VDC±25% |
| Power Consumption | Max. 3.5 W |
| Protection Level | IP67, IK7 |
| Material | Metal |
| IR Range | Up to 65 ft |
| Communication | Up the coax, Protocol: HIKVISION-C (TVI output) |
| Dimensions | Φ 4.4" × 3.2" (Φ 111 mm × 82.4 mm) |
| Weight | Approx. 0.77 lb (350 g) |

Ordering Information

- ULT-C2DRIR28N:** 2 Megapixel Dome, 2.8mm
ULT-C2DRIR36N: 2 Megapixel Dome, 2.8mm
ULT-C2DRIR6N: 2 Megapixel Dome, 6mm

2 MEGAPIXEL | 1080p