



ULT-C2PI37PIR Covert PIR Case with Snap-on Wall Bracket, 1080p Day/Night, 3.7mm, 12VDC

2 Megapixel

Fixed Lens

Day/Night

DC12V

Indoor

Joystick at Camera
OSD Control

Features

- 2 Megapixel (1920 x 1080) Resolution
- 3.7mm Fixed Lens
- Day/Night
- 12VDC Only Operation
- Indoor Only/Non-Functioning
- OSD Joystick at Camera

Image Sensor	1/2.8" 2.4 Megapixel CMOS
Effective Picture Elements	1920x1080 pixels
Video Output	HD-TVI: 1080p 30/25Hz nominal 960H CVBS for test/alignment switchable at camera
Minimum Illumination	0.01LUX @ F1.2 (AGC on)
Lens Furnished	Pinhole lens 3.7mm
S/N Ratio	More than 52 dB
OSD Menu	3-axis joystick on cable
Scanning system	NTSC/PAL selectable
Auto Electronic Shutter	NTSC: 1/60s~1/100,000s, PAL: 1/50s~1/110,000s
Gamma Characteristic	0.45
Day/Night	Internal/Color/Mono
Gain Control	Automatic, adjustable for brightness
White Balance	Auto/Gray
Back/Front Light Compensation	Off/BLC/FLC
Noise Reduction	Off/On for 2DNR, Y, C
Sharpness	Adjustable for Detail, Edge and Saturation
Synchronization	Internal
OSD Language	English and Chinese
Video Output	BNC-F; 1 V p-p / 75 ohm HD-TVI or CVBS
Operating Temperature	14°F to 113°F (-10°C to 45°C)
Humidity	Indoor 85% non-condensing
Power Supply Requirements	12VDC regulated; 300mA recommended
Weight	4.2 oz. / 120 gm
Dimensions	2.72" w x 4.72" H x 1.85" d (69mm w x 120mm h x 47mm d) Add 1.18" (30mm) to depth for mount

Ordering Information

ULT-C2PI37PIR: Non-Functioning PIR, 3.7mm

InVid Tech, reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.

2 MEGAPIXEL | 1080p