



ULT-C2SI37 Smoke Detector Shaped Housing (Non-Functioning)
Day/Night, 12VDC, 3.7mm

- Features
- 2 Megapixel (1920 x 1080) Resolution
 - 3.7mm Fixed Lens
 - Day/Night
 - 12VDC Only Operation
 - Indoor Only/Non-Functioning
 - OSD Joystick at Camera

Image Sensor	1/2.8" 2.4 Megapixel CMOS
Effective Picture Elements	1920x1080 pixels
Video Output	HD-TVI: 1080p 30/25Hz nominal 960H CVBS for test/alignment switchable at camera
Minimum Illumination	0.01LUX @ F1.2 (AGC on)
Lens Furnished	Pinhole lens 3.7mm
S/N Ratio	More than 52 dB
OSD Menu	3-axis joystick on cable
Scanning system	NTSC/PAL selectable
Auto Electronic Shutter	NTSC:1/60s~1/100,000s, PAL:1/50s~1/110,000s
Gamma Characteristic	0.45
Day/Night	Internal/Color/Mono
Gain Control	Automatic, adjustable for brightness
White Balance	Auto/Gray
Back/Front Light Compensation	Off/BLC/FLC
Noise Reduction	Off/On for 2DNR, Y, C
Sharpness	Adjustable for Detail, Edge and Saturation
Synchronization	Internal
OSD Language	English and Chinese
Video Output	BNC-F; 1 V p-p / 75 ohm HD-TVI or CVBS
Operating Temperature	14°F to 113°F (-10°C to 45°C)
Humidity	Indoor 85% non-condensing
Power Supply Requirements	12VDC regulated; 300mA recommended
Weight	12.3 oz. / 350 gm
Dimensions	4.69" Ø x 2.20" H (119mm Ø x 56mm H)

Ordering Information

ULT-C2SI37: Non-Functioning Smoke Detector, 3.7mm

2 MEGAPIXEL | 1080p

InVid Tech, reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.