



ULT-C2TXIR28N

2 Megapixel Outdoor Turret, Fixed Lens, WDR, 131' IR Range, 12VDC

Features

- 2 Megapixel (1920 x 1080) Resolution
- TVI Output
- Fixed Lens
- True Day/Night
- True WDR 120dB
- 131' IR Range
- IP67 Weather Resistant
- -40° Operation
- Analog Video Output
- 12VDC Operation

Camera	
Image Sensor	2.0 megapixel progressive scan CMOS
Signal System	PAL/NTSC
Frame Rate	PAL: 1080p@25fps NTSC: 1080p@30fps
Resolution	1920 (H) x 1080 (V)
Min. illumination	Color: 0.005 Lux @ (F2.0, AGC ON), 0 Lux with IR
Shutter Time	PAL: 1/25 s to 1/50,000 s NTSC: 1/30 s to 1/50,000 s
Slow Shutter	Max.: 16 times
Lens	2.8 mm fixed focal lens
Horizontal Field of View	103.5° (2.8 mm)
Lens Mount	M12
Day & Night	IR cut filter
Angle Adjustment	Pan: 0° to 360°, Tilt: 0° to 75°, Rotate: 0° to 360°
Synchronization	Internal synchronization
WDR (Wide Dynamic Range)	> 120 dB
Menu	
AGC	Support
Day/Night Mode	Auto/Color/BW (Black and White)
White Balance	ATW/MANUAL
Privacy Mask	ON/OFF, 4 programmable privacy masks
Motion Detection	4 programmable motion areas
Backlight Compensation	WDR/BLC/HLC/OFF
3D DNR (Digital Noise Reduction)	On
Language	English, Chinese
Functions	Brightness, Sharpness, Mirror, Smart IR
Interface	
Video Output	1 HD analog output
General	
Operating Conditions	-40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less (non-condensation)
Power Supply	12 VDC±25%
Power Consumption	Max. 4W
Ingress Protection	IP67
Material	Metal
IR Range	Up to 131'
Communication	Up the coax
Dimensions	Φ 110 mm x 93.2 mm (Φ 4.33" x 3.67")
Weight	350 g (0.77 lb.)

Ordering Information

ULT-C2TXIR28N: 2 Megapixel Turret 2.8mm