



**ULT-C3TXIRM2812** 3 Megapixel TVI Outdoor Turret with 2.8-12mm Motorized lens, WDR, 150' EXIR Range, 12VDC

Features

- 3 Megapixel (2052 x 1536) Resolution
- Motorized 2.8-12mm Lens
- True Day/Night
- True WDR 120dB
- 150' IR Range with EXIR Technology
- Up The Cable (UTC) Function
- IP66 Weather Resistant
- Withstand up to -40° Operation
- 12VDC Only Operation

Model Number	ULT-C3TXIRM2812
Image Sensor	3MP CMOS
Signal System	PAL / NTSC
Effective Pixels	2052(H)*1536(V)
Min. Illumination	0.01 Lux @ (F1.2,AGC ON),0 Lux with IR
Shutter Speed	1/25 s to 1/50,000 s
Lens	2.8-12mm @ F1.2 Motorized, Angle of view: 92° – 32°
Auto Iris	Yes
Angle Adjustment	Pan: 0 – 360°, Tilt: 0 – 75°, Rotation: 0 – 360°
Day & Night	IR Cut Filter with Auto Switch
Wide Dynamic Range	120dB True WDR
Synchronization	Internal synchronization
Video Frame Rate	2052*1536@18fps
HD Video Output	1 Analog HD output
S / N Ratio	More than 62dB
Scene	Indoor, Outdoor, Indoor1, Low-Light
Camera ID	On/off (15 characters, position programmable)
AGC	Support
D/N Mode	Color/BW/Smart
White Balance	ATW, MWB
Privacy Mask	On/Off, maximum 8 zones
Motion Detection	On/Off, maximum 4 zones
BLC	Support
Anti-flicker	On/Off
Language	English, Japanese, CHN1, CHN2, Korean, German, French, Italian, Spanish, Polish, Russian, Portuguese, Dutch, Turkish, Hebrew and Arabic
Function	WDR, DNR, Mirror, Smart IR
Working Temperature / Humidity	-40 °F – 140 °F (-40 °C – 60 °C) Humidity 90% or less (non-condensing)
Power Supply	12 VDC
Power Consumption	Max. 6W
Housing	IP66
IR Range	Up to 150 ft
Communication	Up the coax(need UTC controller) Protocol: Pelco-C(-Coaxitron)
Dimensions	5.29 x 4.88 x 4.39in (134.3 x 123.9 x 111.5mm)
Weight	1.57 lbs (700g)

Ordering Information

**ULT-C3TXIRM2812:** 3 Megapixel Turret, 2.8-12mm Motorized

**3 MEGAPIXEL**

*InVid Tech, reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.*