



## ULT-C5DRXIRM2812

5 Megapixel TVI, Outdoor Vandal Dome, 2.8-12mm Motorized, 120' EXIR Range, D-WDR, Dual Voltage

### Features

- 5 Megapixel Resolution (2560 x 1944)
- Motorized 2.8-12mm Lens
- True Day/Night
- 120' IR Range with EXIR Technology
- Withstand up to -40° Operation
- IK10 Vandal Resistant
- Up The Cable (UTC) Function
- Dual Voltage
- IP67 Weather Resistant

Model Number	ULT-C5DRXIRM2812
Image Sensor	1 / 3" Progressive Scan CMOS
video FORMAT	PAL / NTSC
Effective Pixels	2560(H)*1944(V)
Min. Illumination	0.008 Lux @ (F1.2,AGC ON),0 Lux with IR
Shutter speed	1/30s to 1/50,000s
Lens	2.8-12mm @ F1.4, Angle of view: 102° – 31°
Angle Adjustment	Pan: 0 – 355°, Tilt: 0 – 80°
Day & Night	ICR
Wide dynamic range	DWDR
Video Frame Rate	2560 x 1944@20fps
HD Video Output	1 HD-TV1 output
CVBS Output	N/A
Scene	Indoor, Outdoor, Indoor1, LOW-LIGHT
Camera ID	On/off (15 characters, position programmable)
AGC	Support
D/N Mode	Color/BW/Auto
Motion Detection	On/Off, maximum 4 zones
BLC	Support
Anti-flicker	On/off
Working Temperature / Humidity	-40 °C – 60 °C (-40 °F – 140 °F) Humidity 90% or less (non-condensing)
Power Supply	12 VDC, 24 VAC
Power Consumption	Max. 6W
Ratings	IP67, IK10
IR Range	Up to 120 ft
Communication	OSD (UTC Control) via DVR
Dimensions	φ145.3 × 124.2 mm (φ5.72" × 4.89")
Weight	3.53 lbs (880g)

### Mounting Options



IUM-DRPM3  
Pendant Mount



IUM-DRWM5  
Wall Mount



IUM-BRCM1\*\*  
Corner Mount



IUM-POLE  
Pole Mount

### Ordering Information

**ULT-C5DRXIRM2812:** 5 Megapixel Dome, 2.8-12mm

\*\*To use these mounts with the selected cameras drill the holes needed into the mount using the diagram included with the camera. InVid Tech, reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.