



ULT-C5TXIRM2812N

5 Megapixel TVI, Outdoor Turret, 2.7-13.5mm Motorized, 131' EXIR Range, up to -40, D-WDR, 12VDC, White Housing

Features

- 5 Megapixel Resolution (2560 x 1944)
- True Day/Night
- 12VDC Only Operation
- Motorized 2.7-13.5mm Lens
- Withstand up to -40° Operation
- 131' IR Range
- IP67 Weather Resistant
- Up The Cable (UTC) Function
- Through InVid Tech DVR: Free App, CMS & MAC Client

Model Number	ULT-C5TXIRM2812N
Image Sensor	5 MP CMOS Image Sensor
Resolution	2560 (H) × 1944 (V)
Min. Illumination	Color: 0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR
Shutter Time	PAL: 1/25 s to 1/50,000 s, NTSC: 1/30 s to 1/50,000 s
Lens	2.7 mm to 13.5 mm motorized vari-focal lens
Horizontal Field of View	95.7° to 29.1°
Lens Mount	φ 14
Day & Night	IR cut filter
Angle Adjustment	Pan: 0° to 360°; Tilt: 0° to 75°; Rotate: 0° to 360°
Synchronization	Internal synchronization
Frame Rate	PAL: 5 MP@20fps, 4 MP@25fps, 1080p@25fps, NTSC: 5 MP@20fps, 4 MP@30fps, 1080p@30fps
Menu	
AGC	Support
D/N Mode	Auto/Color/BW (Black and White)
White Balance	ATW/MWB
BLC	Support
DWDR (Digital Wide Dynamic Range)	Support
Functions	Brightness, Sharpness, DNR, Mirror, Smart IR
Interface	
Video Output	1 HD analog output
Switch Button	TVI/AHD/CVI/CVBS
General	
Operating Conditions	-40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less (non-condensation)
Power Supply	12 VDC ±25%
Power Consumption	Max. 6.3 W
Protection Level	IP67
Material	Metal
IR Range	Up to 40 m
Communication	Up the coax, Protocol: UTC-C (TVI output)
Dimensions	4.88" × 5.29" × 4.38" (123.86 mm × 134.3 mm × 110.11 mm)
Weight	Approx. 1.28 lb. (580 g)

Ordering Information

ULT-C5TXIRM2812N: 5 Megapixel, 2.7-13.5 Lens

**To use these mounts with the selected cameras drill the holes needed into the mount using the diagram included with the camera. InVid Tech, reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.