



ULT-ALLBXIRWL

2 Megapixel TVI/AHD/CVI/Analog Outdoor Turret with 24/7 Color, 131' White Light Motion Sensor, WDR, up to -40°, 12VDC

Features

- Full Color Picture 24/7 - Even in low light!
- 2 Megapixel Resolution
TVI: 2 MP, AHD: 2 MP, CVI: 2 MP, Analog: 960H
- All-in-One Technology (TVI/AHD/CVI/Analog 960h)
- Fixed Lens
- White Light Motion Sensor up to 131'
- True WDR 130dB
- Up The Cable (UTC) Function
- IP67 Weatherproof
- Withstand up to -40° F Operation
- 12VDC Operation
- Through InVid Tech DVR: Free App, CMS & MAC Client

Specifications	ULT-ALLBXIRWL
Image Sensor	2MP CMOS
Resolution	1920×1080
Min. Illumination	0.0005 Lux @ (F1.0, AGC ON), 0 Lux with White Light
Shutter Time	PAL: 1/25 s to 1/50,000 s NTSC: 1/30 s to 1/50,000 s
Slow Shutter	Max. 16 times
Lens	2.8mm, 4mm fixed lens
Horizontal FOV	109°(2.8 mm), 67° (4 mm)
Lens Mount	M16
Strobe Light Alarm	Yes
Day & Night	Color
WDR (Wide Dynamic Range)	≥130 dB
Angle Adjustment	Pan: 0 to 360°, Tilt: 0 to 90°, Rotation: 0 to 360°
White Light	Auto/Manual
Image Mode	STD/HIGH-SAT
AGC	Yes
Day/Night Mode	Color
White Balance	Auto/Manual
AE (Auto Exposure) Mode	WDR/BLC/HLC/Global/HLS/Anti-banding
Privacy Marks	4 programmable privacy masks
Motion Detection	4 programmable motion areas
Noise Reduction	3D DNR
Language	English
Function	Brightness, Sharpness, Mirror, Smart Light
Video Output	Switchable TVI/AHD/CVI/CVBS
Operating Conditions	-40 °C to 60 °C (-40 °F to 140 °F), humidity 90% or less (non-condensing)
Power Supply	12 VDC ± 25%
Power Consumption	Max. 4.9W
Protection Level	IP67
Material	Front Cover: Metal, Main Body: Plastic
White Light Range	Up to 131'
Communication	UTC-C
Dimensions	3.25" × 3.04" × 8.49" (82.6 × 77.1 × 215.7mm)
Weight	Approx. 0.91 lb (415g)

Ordering Information

ULT-ALLBXIR28WL: 2 Megapixel Bullet, 2.8mm

ULT-ALLBXIR4WL: 2 Megapixel Bullet, 4mm