



## VIS-P2BXIRA65143

2 Megapixel Starlight IP Plug & Play, Outdoor Bullet, 6.5-143mm Auto-Focus Motorized, 656' EXIR Range, SD Card Slot, 24VAC/PoE+

### Features

- 2 Megapixel (1920x1080)
- Motorized Auto-Focus 6.5-143mm Lens
- Ultra H.265/H.265/H.264/MJPEG
- True Day/Night
- True WDR 120dB
- Smart Analytics
- Cloud Upgradable
- Starlight Illumination
- 60 FPS Recording and Live
- Smart EXIR Range up to 656'
- Starlight Illumination
- CVBS Video Output
- Micro SD Slot: Up to 256GB
- Audio Input/Output
- IP67 Weatherproof
- Withstand up to -40F Operation
- 24VAC/PoE+ Operation
- ONVIF
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS)
- Free MAC client



### Ordering Information

**VIS-P2BXIRA65143:** 2 Megapixel, Motorized A/F 6.5-143mm

InVid Tech, reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.

Camera	
Sensor	1/1.8", progressive scan, 2.0 megapixel, CMOS
Lens	6.5 ~ 143 mm, AF automatic focusing and motorized zoom lens
Optical Zoom	22
	Lens Detect (ft) Observe (ft) Recognize (ft) Identify (ft)
DORI Distance	6.5mm: 255 (78m) 102 (31.2m) 51 (15.6m) 26 (7.8m)
	143mm: 5629 (1716m) 2251 (686.4m) 1126 (343.2m) 563 (171.6m)
Angle of view(H)	59°~3°
Angle of View (V)	34.6°~1.6°
Angle of View (O)	76.7°~3.7°
Adjustment angle	Pan: 0°~360°, Tilt: 0°~90°, Rotate: 0°~360°
Shutter	Auto/Manual, 1/1~1/100000 s
Minimum Illumination	Color: 0.001 Lux (F1.5, AGC ON), 0 Lux with IR
Iris	Auto/Manual, F1.5~F3.4, DC-Iris
Day/Night	IR-cut filter with auto switch (ICR)
Digital noise reduction	2D/3D DNR
S/N	>52 dB
IR Range	up to 656 ft (200 m) IR range
Defog	Digital Defog
WDR	120dB
Video	
Video Compression	Ultra 265, H.265, H.264, MJPEG
H.264 code profile	Baseline profile, Main Profile, High Profile
Frame Rate	Main Stream: 2MP (1920x1080): Max. 60 fps; Sub Stream: 2MP (1920x1080): Max. 60 fps; Third Stream: D1 (720x576): Max. 60 fps
9:16 Corridor Mode	Supported
ROI	Supported
HLC	Supported
BLC	Supported
OSD	Up to 8 OSDs
Motion Detection	Up to 4 areas
Privacy Mask	Up to 8 areas
Smart	
Behavior Detection	Intrusion, cross line, motion detection
Intrusion	Enter and loiter in a pre-defined virtual region
Cross line	Cross a pre-defined virtual line
Motion detection	Moving within a pre-defined virtual region
Recognition:	Face detection, Audio detection
Intelligent Identification	Defocus, Scene Change, Object Left, Object Moving
Statistical Analysis	People counting
General Function	Watermark, IP Address Filtering, Tampering Alarm, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication
Audio	
Audio Compression	G.711
Two-way audio	Supported
Suppression	Supported
Sampling Rate	8 KHZ
Storage	
Edge Storage	Micro SD, up to 256 GB
Network Storage	ANR
Network	
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP
Compatible Integration	ONVIF(Profile S, Profile G), API
Interface	
	Audio cable
Audio I/O	1 Input: impedance 35 kΩ; amplitude 2 V [p-p] 1 Output: impedance 600 Ω; amplitude 2 V [p-p]
Alarm I/O	2/1
Serial Port	1 RS485
Network	1 RJ45 10M/100M Base-TX Ethernet
Video Output	1 BNC, impedance 75 Ω; amplitude 1 V [p-p]
General	
Power	24 V AC ±25%, PoE+: PoE(IEEE 802.3at) (PSE Required, sold separately) Power consumption: Max 21W
Dimensions (L × W × H)	15.6" × 5.4" × 4.4" (396.5 × 137 × 112mm)
Weight	8.2 lb (3.7 kg)
Working Environment	-40°F ~ 140°F (-40°C ~ +60°C), Humidity ≤ 95% RH(non-condensing)
Ingress Protection	IP67
Reset Button	Supported
Certification	UL