



VIS-P2BXIRPT36-32G

2 Megapixel IP Plug & Play, Outdoor Bullet, Motorized 3-6mm Pan/Tilt, PoE/DC12V

Features

- 2 Megapixel (1920x1080) Resolution
- H.265/H.264/MJPEG Compression
- True Day/Night
- Motorized Auto-Focus 3-6mm Lens
- 30 FPS Recording and Live
- D-WDR
- Smart Analytics
- Smart EXIR Range up to 328'
- Built-In 32GB eMMC Card
- Audio Input/Output
- IP66 Weather Resistant
- 12VDC/PoE Operation
- ONVIF
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) to manage multiple units & sites from a single platform
- Free MAC client software available to manage your system from your Apple computer

Ordering Information

VIS-P2BXIRPT36-32G: 2 Megapixel, Motorized 3-6mm

Camera	VIS-P2BXIRPT36-32G
Sensor	1/3", progressive scan ,2.0 megapixel, CMOS
Lens	3 ~ 6 mm, AF automatic focusing and motorized zoom lens
Digital Zoom	16
Optical Zoom	2
DORI Distance	Lens: 3mm 219'(Detect), 88'(Observe), 44'(Recognize), 22'(Identify) Lens: 6mm 442'(Detect), 177'(Observe), 88'(Recognize), 44'(Identify)
Angle of view(H)	90.9°~51.5°
Angle of View (V)	39.6°~20.4°
Angle of View (O)	101.8°~63.3°
Shutter	Auto/Manual, 1/6s ~ 1/100000s
Minimum Illumination	Color: 0.02Lux (F1.8, AGC ON) 0 Lux with IR on
Iris	Auto/Manual, F1.8
Day/Night	IR-cut filter with auto switch (ICR)
Digital noise reduction	2D/3D DNR
S/N	>52dB
IR Range	Up to 100m (328 ft) IR range
Defog	Digital Defog
WDR	DWDR
Video	
Video Compression	Ultra 265,H.265, H.264, MJPEG
H.264 code profile	Baseline profile, Main Profile, High Profile
Frame Rate	Main Stream: 2MP (1920x1080): Max. 30 fps; Third Stream:D1(720x576) : Max. 30 fps; Sub Stream: 2MP (1920x1080): Max. 30 fps;
HLC	Supported
BLC	Supported
OSD	Up to 8 OSDs
Privacy Mask	Up to 8 areas
ROI	Up to 8 areas
Motion Detection	Up to 4 areas
Smart	
Behavior Detection	Intrusion, cross line, motion detection
Intrusion	Enter and loiter in a pre-defined virtual region
cross line	Cross a pre-defined virtual line
motion detection	Moving within a pre-defined virtual region
Recognition:	Face detection, Audio detection
Intelligent Identification	Defocus, Scene Change
Statistical Analysis	People counting
General Function	Watermark, IP Address Filtering, Tampering Alarm, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication
Audio	
Audio Compression	G.711
Two-way Audio	Supported
Suppression	Supported
Sampling Rate	8 KHZ
Storage	
Edge Storage	Built-in 32 GB eMMC
Network Storage	ANR
Network	
Protocol	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP
Compatibility	ONVIF(Profile S), API
Structure	
Pan Range	250°
Pan Speed	0.1°/s ~ 15°/s Preset speed: 15°/s
Tilt Range	-50° ~ 50°
Tilt Speed	0.1°/s ~5°/s Preset speed: 5°/s
Number of Presets	400
Patrol	Up to 16 patrols, up to 32 presets per patrol, Note: The Total Number Of Patrols and Patterns Is 16
Interface	
Audio I/O	3.5 mm connector, Input: impedance 35 kΩ; amplitude 2 V (p-p) ,Output: impedance 600 Ω; amplitude 2 V (p-p)
Alarm I/O	2 / 1
Network	1 RJ45 10M/100M adaptive Ethernet
General	
Power	12 V DC±25%, PoE (IEEE802.3at) Power consumption: Max. 17.23 W
Dimensions	357 mm × 106 mm × 194 mm (14.1" × 4.2" × 7.7")
Weight	1.16 kg (2.6 lb)
Working Environment	-35°C to +60°C (-31°F to 140°F), Humidity:10%~95% RH(non-condensing)
Ingress Protection	IP66