



VIS-P4BXIR-16G

4 Megapixel IP Plug & Play, Outdoor Bullet, 98' EXIR Range, Built-in 16 GB eMMC Card, PoE/DC12V

Features

- 4 Megapixel (2592 x 1520) Resolution
- Fixed Lens
- H.265/H.264/MJPEG Compression
- True Day/Night
- True WDR 120dB
- Smart Analytics
- Smart EXIR Range up to 98'
- Built-In 16GB eMMC Card
- IP67 Weather Resistant
- 12VDC/PoE Operation
- ONVIF
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) to manage multiple units & sites from a single platform
- Free MAC client software available to manage your system from your Apple computer

Camera	VIS-P4BXIR
Sensor	1/3", progressive scan, 4.0 megapixel, CMOS
Lens	3.6mm@F1.8, 6.0mm@F1.8, 12.0mm@F1.8
DORI Distance	3.6mm: 265' (Detect), 106' (Observe), 53' (Recognize), 26' (Identify) 6mm: 442' (Detect), 177' (Observe), 88' (Recognize), 44' (Identify) 12mm: 885' (Detect), 354' (Observe), 177' (Recognize), 88' (Identify)
Angle of View(H)	3.6mm: 86.4°, 6.0mm: 49.9°, 12.0mm: 24.1°
Angle of View (V)	3.6mm: 43.6°, 6.0mm: 27°, 12.0mm: 13.7°
Angle of View (O)	3.6mm: 112.3°, 6.0mm: 61.4°, 12.0mm: 29.6°
Adjustment angle	Pan: 0°~360°, Tilt: 0°~90°, Rotate: 0°~360°
Shutter	Auto/Manual, 1/6~1/100000 s
Minimum Illumination	Colour: 0.02 Lux (F1.8, AGC ON), 0 Lux with IR on
Day/Night	IR-cut filter with auto switch (ICR)
Digital noise reduction	2D/3D DNR
S/N	>55dB
IR Range	Up to 30m (98 ft) IR range
Defog	Digital Defog
WDR	120dB
Video	
Video Compression	Ultra 265, H.265, H.264, MJPEG
H.264 code profile	Baseline profile, Main Profile, High Profile
Frame Rate	Main Stream: 4MP (2592x1520): Max. 20 fps 4MP (2560x1440): Max. 25 fps 3MP (2048x1520): Max. 30 fps; Sub Stream: 2MP (1920x1080): Max. 30 fps; Third Stream: D1 (720x576) : Max. 30fps
9:16 Corridor Mode	Supported
HLC	Supported
BLC	Supported
OSD	Up to 8 OSDs
Privacy Mask	Up to 8 areas
ROI	Up to 8 areas
Motion Detection	Up to 4 areas
Smart	
Behavior Detection	Intrusion, cross line, motion detection
Intrusion	Enter and loiter in a pre-defined virtual region
cross line	Cross a pre-defined virtual line
motion detection	Moving within a pre-defined virtual region
Recognition	Face detection, Audio detection
Intelligent Identification	Defocus, Scene Change
Statistical Analysis	People counting
General Function	Watermark, IP Address Filtering, Tampering Alarm, Access Policy, ARP Protection, RTSP Authentication, User Authentication
Network	
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP
Compatible Integration	ONVIF(Profile S), API
Storage	
Edge Storage	Built-in 16 GB eMMC
Interface	
Network	1 RJ45 10M/100M Base-TX Ethernet
General	
Power	12 V DC±25%, PoE (IEEE802.3 af), Power consumption: Max 6.4 W
Dimensions (L x W x H)	157.3 x 62.4 x 63 mm (6.2" x 2.5" x 2.5")
Weight	0.45kg(0.99 lb)
Working Environment	-35°C ~ +60°C (-31°F ~ 140°F), Humidity : 10%~95% RH(non-condensing)
Ingress Protection	IP67
Reset Button	Supported

4 MEGAPIXEL PLUG & PLAY

Ordering Information

VIS-P4BXIR36-16G: 4 Megapixel Bullet, 3.6mm, 16 GB Storage