



## VIS-P4BXIR4LC

4 Megapixel IP Plug & Play, Outdoor Bullet, Fixed Lens, 98' EXIR Range, PoE/DC12V

### Features

- 4 Megapixel (2592 x 1520)
- Fixed Lens
- Ultra H.265/H.265/H.264/MJPEG
- True Day/Night
- D-WDR
- Cloud Upgradeable
- Smart EXIR Range up to 98'
- IP67 Weather Resistant
- 12VDC/PoE Operation
- ONVIF
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS)
- Free MAC client

Camera	VIS-P4BXIR4LC
Sensor	1/3", 4 Megapixel, progressive scan, CMOS
Lens	4.0mm@F2.0, 6.0mm@F2.0
Dori Distance	4.0: 196ft. (Detect), 78ft. (Observe), 39ft. (Recognize), 19ft. (Identify) 6.0: 295ft. (Detect), 118ft. (Observe), 59ft. (Recognize), 29ft. (Identify)
Angle of View(H)	4.0mm: 78.9°, 6.0mm: 49.9°
Angle of View(V)	4.0mm: 39.6°, 6.0mm: 27.0°
Angle of View(O)	4.0mm: 97.0°, 6.0mm: 57.7°
Adjustment Angle	Pan: 0-360, Tilt: 0-90, Rotate: 0-360
Shutter	Auto/Manual, 1~1/100000 s
Min. Illumination	Colour: 0.03 Lux (F2.0, AGC ON), 0 Lux with IR on
Digital Noise Reduction	2D/3D DNR
IR Range	Up to 30m (98 ft) IR range
Day/Night	IR-cut filter with auto switch (ICR)
S/N	>52 dB
WDR	DWDR
<b>Video</b>	
Video Compression	Ultra 265,H.265, H.264, MJPEG
H.264 code profile	Baseline profile, Main Profile, High Profile
Frame Rate	Main Stream:4MP (2592*1520): Max. 20 fps; Sub Stream:720P (1280*720): Max. 30 fps; Third Stream:D1 (720*576): Max. 30 fps
HLC	Supported
BLC	Supported
OSD	Up to 4 OSDs
Privacy Mask	Up to 8 areas
ROI	Up to 2 areas
Motion Detection	Up to 4 areas
<b>Network</b>	
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL
Compatible Integration	ONVIF (Profile S), API
<b>Interface</b>	
Network	10M/100M Base-TX Ethernet
<b>General</b>	
Power	12 V DC±25%, PoE (IEEE802.3 af) Power consumption: Max 4W
Dimensions (L x W x H)	167.3 x 62.9 x 62.7MM (6.6" x 2.5" x 2.5")
Weight	0.37 kg (0.81 lb)
Working Environment	-35°C ~ +60°C (-31°F ~ 140°F), Humidity ≤ 95% RH(non-condensing)
Ingress Protection	IP67

### Ordering Information

**VIS-P4BXIR4LC:** 4 Megapixel Bullet, 4mm  
**VIS-P4BXIR6LC:** 4 Megapixel Bullet, 6mm