



## VIS-P4DRXIRLC

4 Megapixel IP Plug & Play, Outdoor Rugged Dome, Fixed Lens, 98' EXIR Range, SD Card Slot, PoE/DC 12V

### Features

- 4 Megapixel (2592 x 1520) Resolution
- Fixed Lens
- Ultra H.265/H.265/H.264/MJPEG Compression
- True Day/Night
- D-WDR
- Cloud Upgradeable
- Smart EXIR Range up to 98'
- IK10 Vandal Resistant
- IP67 Weather Resistant
- 12VDC/PoE Operation
- ONVIF
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) to manage multiple units & sites from a single platform
- Free MAC client software available to manage your system from your Apple computer

Camera	VIS-P4DRXIRLC
Sensor	1/3", progressive scan, 4.0 megapixel, CMOS
Lens	2.8mm@F2.0, 4.0mm@ F2.0
DORI Distance	2.8mm: 2.8mm: 137' (Detect), 55' (Observe), 28' (Recognize), 14' (Identify) 4mm: 4mm: 197' (Detect), 78' (Observe), 39' (Recognize), 20' (Identify)
Angle of View (H)	2.8mm: 104.4°, 4mm: 78.9°
Angle of View (V)	2.8mm: 54.4°, 4mm: 39.6°
Angle of View (O)	2.8mm: 135.7°, 4mm: 97.0°
Adjustment angle	Pan: 0°~360°, Tilt: 0°~75°
Shutter	Auto/Manual, 1~1/100000 s
Minimum Illumination	Colour: 0.03 Lux (F2.0, AGC ON), 0Lux with IR
Day/Night	IR-cut filter with auto switch (ICR)
Digital noise reduction	2D/3D DNR
S/N	>52dB
IR Range	Up to 30m (98 ft) IR range
Defog	Digital Defog
WDR	DWDR
Video	
Video Compression	Ultra 265,H.265,H.264,MJPEG
H.264 code profile	Baseline profile, Main Profile, High Profile
Frame Rate	Main Stream:4MP (2592*1520): Max. 20 fps; Sub Stream:720P (1280*720): Max. 30 fps; Third Stream:D1 (720*576): Max. 30 fps
HLC	Supported
BLC	Supported
OSD	Up to 4 OSDs
Privacy Mask	Up to 8 areas
ROI	Up to 2 areas
Motion Detection	Up to 4 areas
Network	
Protocols	IPv4,IGMP,ICMP,ARP,TCP,UDP,DHCP, RTP,RTSP,RTCP,DNS,DDNS,NTP,FTP,UPnP,HTTP,HTTPS,SMTP, SSL
Compatible Integration	ONVIF(Profile S), API
Interface	
Network	1 RJ45 100M Base-TX Ethernet
General	
Power	DC12V±25%, PoE (IEEE802.3 af) Power consumption: Max.4w
Dimensions (Ø x H)	Φ109 x 81mm (Ø5.8" x 4.4")
Weight	0.35kg (0.77lb)
Working Environment	-30°C ~ +60°C (-22°F ~ 140°F), Humidity :10%~90% RH(non-condensing)
Ingress Protection	IP67
Vandal Resistant	IK10

### Ordering Information

**VIS-P4DRXIR28LC:** 4 Megapixel Dome, 2.8mm

**VIS-P4DRXIR4LC:** 4 Megapixel Dome, 4mm