



## VIS-P4TXIRLC

4 Megapixel IP Plug & Play, Outdoor Turret, Fixed Lens, 98' EXIR Range, PoE/DC12V

### Features

- 4 Megapixel (2592 x 1520) Resolution
- Fixed Lens
- Ultra H.265/H.265/H.264/MJPEG Compression
- True Day/Night
- D-WDR
- Cloud Upgradeable
- Smart EXIR Range up to 98'
- IP67 Weather Resistant
- 12VDC/PoE Operation
- ONVIF
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) to manage multiple units & sites from a single platform
- Free MAC client software available to manage your system from your Apple computer

|                         |  |
|-------------------------|--|
| Camera                  | VIS-P4TXIRLC   |
| Sensor                  | 1/3", progressive scan, 4.0 megapixel, CMOS  |
| Lens                    | 2.8mm@F2.0, 4.0mm@ F2.0  |
| DORI Distance           | 2.8mm: 2.8mm: 137' (Detect), 55' (Observe), 28' (Recognize), 14' (Identify)<br>4mm: 4mm: 197' (Detect), 78' (Observe), 39' (Recognize), 20' (Identify) |
| Angle of View (H)       | 2.8mm: 104.4°, 4mm: 78.9°  |
| Angle of View (V)       | 2.8mm: 54.4°, 4mm: 39.6°   |
| Angle of View (O)       | 2.8mm: 135.7°, 4mm: 97.0°  |
| Adjustment angle        | Pan: 0°~360°, Tilt: 0°~90, Rotate: 0°~360°   |
| Shutter                 | Auto/Manual, 1~1/100000 s  |
| Minimum Illumination    | Color: 0.03 Lux (F2.0, AGC ON), 0 Lux with IR  |
| Day/Night               | IR-cut filter with auto switch (ICR)   |
| Digital noise reduction | 2D/3D DNR  |
| S/N                     | >52dB  |
| IR Range                | Up to 30m (98 ft) IR range   |
| WDR                     | DWDR   |
| Video                   |  |
| Video Compression       | Ultra 265,H.265,H.264,MJPEG  |
| Frame Rate              | Main Stream:4MP (2592*1520): Max. 20 fps;<br>Sub Stream:720P (1280*720): Max. 30 fps;<br>Third Stream:D1 (720x576): Max. 30 fps                        |
| HLC                     | Supported  |
| BLC                     | Supported  |
| OSD                     | Up to 4 OSDs   |
| Privacy Mask            | Up to 8 areas  |
| ROI                     | Up to 2 areas  |
| Motion Detection        | Up to 4 areas  |
| Network                 |  |
| Protocols               | IPv4,IGMP,ICMP,ARP,TCP,UDP,DHCP, RTP,RTSP,RTCP,DNS,DDNS,NTP,FTP,UPnP,HTTP,HTTPS,SMTP, SSL  |
| Compatible Integration  | ONVIF(Profile S), API  |
| Interface               |  |
| Network                 | 10/100M Base-TX Ethernet   |
| General                 |  |
| Power                   | 12 V DC±25%, PoE (IEEE802.3 af)<br>Power consumption: Max. 4w  |
| Dimensions (Ø x H)      | Φ118x 96 mm (Φ4.6" x 3.8")   |
| Weight                  | 0.35kg (0.77lb)  |
| Working Environment     | -30°C ~ +60°C (-22°F ~ 140°F), Humidity : 10%~90% RH(non-condensing)   |
| Ingress Protection      | IP67   |

### Ordering Information

**VIS-P4TXIR28LC:** 4 Megapixel Turret, 2.8mm

**VIS-P4TXIR4LC:** 4 Megapixel Turret, 4mm