



## VIS-P5BXIRLC

5 Megapixel IP Plug & Play, Outdoor Bullet, Fixed Lens, 98' EXIR Range, PoE/DC12V

### Features

- 5 Megapixel (2592 x 1944) Resolution
- Fixed Lens
- Ultra H.265/H.265/H.264/MJPEG Compression
- True Day/Night
- D-WDR
- Cloud Upgradeable
- Smart EXIR Range up to 98'
- IP67 Weather Resistant
- 12VDC/PoE Operation
- ONVIF
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) to manage multiple units & sites from a single platform
- Free MAC client software available to manage your system from your Apple computer

Camera	VIS-P4BXIR5LC
Sensor	1/2.7", 5.0 megapixel, progressive scan, CMOS
Lens	4.0mm@F2.0, 6.0mm@F2.0
DORI Distance	4.0: 196ft. (Detect), 78ft. (Observe), 39ft. (Recognize), 19ft. (Identify) 6.0: 295ft. (Detect), 118ft. (Observe), 59ft. (Recognize), 29ft. (Identify)
Angle of View(H)	4.0mm: 79.7°, 6.0mm: 50.5°
Angle of View(V)	4.0mm: 51.8°, 6.0mm: 35.9°
Angle of View(O)	4.0mm: 98.0°, 6.0mm: 62.1°
Adjustment Angle	Pan: 0-360°, Tilt: 0-90°, Rotate: 0-360°
Shutter	Auto/Manual, 1~1/100000 s
Min. Illumination	Color: 0.01 Lux (F2.0, AGC ON), 0 Lux with IR on
Digital Noise Reduction	2D/3D DNR
IR Range	Up to 30m (98 ft) IR range
Day/Night	IR-cut filter with auto switch (ICR)
S/N	>52 dB
WDR	DWDR
<b>Video</b>	
Video Compression	Ultra 265,H.265, H.264, MJPEG
H.264 code profile	Baseline profile, Main Profile, High Profile
Frame Rate	Main Stream:4MP (2592*1944): Max. 15 fps; Sub Stream:720P (1280*720): Max. 20 fps;
HLC	Supported
BLC	Supported
OSD	Up to 4 OSDs
Privacy Mask	Up to 8 areas
ROI	Up to 2 areas
Motion Detection	Up to 4 areas
<b>Network</b>	
Protocols	IPV4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL
Compatible Integration	ONVIF (Profile S), API
<b>Interface</b>	
Network	10M/100M Base-TX Ethernet
<b>General</b>	
Power	12 V DC±25%, PoE (IEEE802.3 af) Power consumption: Max 4W
Dimensions (L x W x H)	167.3 x 62.9 x 62.7MM (6.6" x 2.5" x 2.5")
Weight	0.37 kg (0.81 lb)
Working Environment	-30°F ~ 60°F (-3-22°C ~ +140°C), Humidity ≤ 95% RH(non-condensing)
Ingress Protection	IP67

### Ordering Information

**VIS-P5BXIR4LC:** 5 Megapixel Bullet, 4mm  
**VIS-P5BXIR6LC:** 5 Megapixel Bullet, 6mm