



VIS-P5DRXIRLC

5 Megapixel IP Plug & Play, Outdoor Rugged Dome, Fixed Lens, 98' EXIR Range, PoE/DC12V

Features

- 5 Megapixel (2592 x 1944) Resolution
- Fixed Lens
- Ultra H.265/H.265/H.264/MJPEG Compression
- True Day/Night
- D-WDR
- Cloud Upgradeable
- Smart EXIR Range up to 98'
- IK10 Vandal Resistant
- IP67 Weather Resistant
- 12VDC/PoE Operation
- ONVIF
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) to manage multiple units & sites from a single platform
- Free MAC client software available to manage your system from your Apple computer

Camera	VIS-P5DRXIRLC
Sensor	1/2.7", progressive scan, 5.0 megapixel, CMOS
Lens	2.8mm@F2.0, 4.0mm@ F2.0
DORI Distance	2.8mm: 2.8mm: 137' (Detect), 55' (Observe), 28' (Recognize), 14' (Identify) 4mm: 4mm: 197' (Detect), 78' (Observe), 39' (Recognize), 20' (Identify)
Angle of View (H)	2.8mm: 105.3°, 4mm: 79.7°
Angle of View (V)	2.8mm: 69.5°, 4mm: 51.8°
Angle of View (O)	2.8mm: 136.9°, 4mm: 98.0°
Adjustment angle	Pan: 0°~360°, Tilt: 0°~75°
Shutter	Auto/Manual, 1~1/100000 s
Minimum Illumination	Colour: 0.01 Lux (F2.0, AGC ON), 0Lux with IR
Day/Night	IR-cut filter with auto switch (ICR)
Digital noise reduction	2D/3D DNR
S/N	>52dB
IR Range	Up to 30m (98 ft) IR range
WDR	DWDR
Video	
Video Compression	Ultra 265,H.265,H.264,MJPEG
H.264 code profile	Baseline profile, Main Profile, High Profile
Frame Rate	Main Stream:5MP (2592*1944): Max. 15 fps; Sub Stream:720P (1280*720): Max.20 fps;
HLC	Supported
BLC	Supported
OSD	Up to 4 OSDs
Privacy Mask	Up to 8 areas
ROI	Up to 2 areas
Motion Detection	Up to 4 areas
Network	
Protocols	IPv4,IGMP,ICMP,ARP,TCP,UDP,DHCP, RTP,RTSP,RT-CP,DNS,DDNS,NTP,FTP,UPnP,HTTP,HTTPS,SMTP, SSL
Compatible Integration	ONVIF(Profile S), API
Interface	
Network	10M/100M Base-TX Ethernet
General	
Power	DC12V±25%, PoE (IEEE802.3 af) Power consumption: Max.4w
Dimensions (Ø x H)	Φ109 x 81mm (Ø4.3" x 3.2")
Weight	0.35kg (0.77lb)
Working Environment	-30°C ~ +60°C (-22°F ~ 140°F), Humidity : 10%~90% RH(non-condensing)
Ingress Protection	IP67
Vandal Resistant	IK10

Ordering Information

VIS-P5DRXIR28LC: 5 Megapixel Dome, 2.8mm

VIS-P5DRXIR4LC: 5 Megapixel Dome, 4mm