

4 Channel Kits with Choice of Bullet or Turret

Choose your 4 Megapixel Camera



VIS-P4BXIR4LC

4 Megapixel IP Plug & Play, Outdoor Bullet, Fixed Lens, 98' EXIR Range, PoE/DC12V

OR



VIS-P4TXIR4LC

4 Megapixel IP Plug & Play, Outdoor Turret, Fixed Lens, 98' EXIR Range, PoE/DC12V

Bullet & Turret Features

- 4 Megapixel (2592 x 1520) Resolution
- Fixed Lens
- Ultra H.265/H.265/H.264/MJPEG Compression
- True Day/Night
- D-WDR
- Cloud Upgradeable
- Smart EXIR Range up to 98'
- IP67 Weather Resistant
- 12VDC/PoE Operation
- ONVIF
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS)
- Free MAC client



Get a 4 Ch NVR and Cable Included



VN1A-4X4

4 Ch NVR with 4 Plug & Play Ports, 40 Mbps, 1 HD Bay



Includes (4) Plug & Play Cat5 Cables 60 Ft Each

NVR Features

- Up to 8 Megapixel Resolution Recording
- 4 Plug & Play Ports for easy camera setup PoE (Power Over Ethernet) available on all ports
- 40 Mbps Bit Rate Input
- Supports up to 4 channel simultaneous playback
- Works with ONVIF or other supported IP cameras
- Upgrade your recorder via the Cloud
- Local HDMI main monitor output with 4K Support
- Local VGA main monitor output up to 1080p
- EZ Vision Stream Connect for Networking
- Smart Analytic Support
- Multiple video search options including Smart Search for quick retrieval of footage.
- Ultra H.265/H.265/H.264 video compression
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS)
- Free MAC client



4 Ch NVR with 4 Bullets

VIS-4KIT-1: 4 Ch NVR with 4 Bullets, No Drive

VIS-4KIT-1/1TB: 4 Ch NVR with 4 Bullets, 1 TB

VIS-4KIT-1/2TB: 4 Ch NVR with 4 Bullets, 2 TB

VIS-4KIT-1/4TB: 4 Ch NVR with 4 Bullets, 4 TB

4 Ch NVR with 4 Turrets

VIS-4KIT-2: 4 Ch NVR with 4 Turrets, No Drive

VIS-4KIT-2/1TB: 4 Ch NVR with 4 Turrets, 1 TB

VIS-4KIT-2/2TB: 4 Ch NVR with 4 Turrets, 2 TB

VIS-4KIT-2/4TB: 4 Ch NVR with 4 Turrets, 4 TB

4 Ch NVR with 2 Bullets & 2 Turrets

VIS-4KIT-3: 4 Ch NVR with 2 Bullets & 2 Turrets, No Drive

VIS-4KIT-3/1TB: 4 Ch NVR with 2 Bullets & 2 Turrets, 1 TB

VIS-4KIT-3/2TB: 4 Ch NVR with 2 Bullets & 2 Turrets, 2 TB

VIS-4KIT-3/4TB: 4 Ch NVR with 2 Bullets & 2 Turrets, 4 TB



VIS-P4TXIRLC

4 Megapixel IP Plug & Play, Outdoor Turret, Fixed Lens, 98' EXIR Range, PoE/DC12V

Features

- 4 Megapixel (2592 x 1520) Resolution
- Fixed Lens
- Ultra H.265/H.265/H.264/MJPEG Compression
- True Day/Night
- D-WDR
- Cloud Upgradeable
- Smart EXIR Range up to 98'
- IP67 Weather Resistant
- 12VDC/PoE Operation
- ONVIF
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) to manage multiple units & sites from a single platform
- Free MAC client software available to manage your system from your Apple computer

Camera	VIS-P4TXIRLC
Sensor	1/3", progressive scan, 4.0 megapixel, CMOS
Lens	2.8mm@F2.0, 4.0mm@ F2.0
DORI Distance	2.8mm: 2.8mm: 137' (Detect), 55' (Observe), 28' (Recognize), 14' (Identify) 4mm: 4mm: 197' (Detect), 78' (Observe), 39' (Recognize), 20' (Identify)
Angle of View (H)	2.8mm: 104.4°, 4mm: 78.9°
Angle of View (V)	2.8mm: 54.4°, 4mm: 39.6°
Angle of View (O)	2.8mm: 135.7°, 4mm: 97.0°
Adjustment angle	Pan: 0°~360°, Tilt: 0°~90, Rotate: 0°~360°
Shutter	Auto/Manual, 1~1/100000 s
Minimum Illumination	Color: 0.03 Lux (F2.0, AGC ON), 0 Lux with IR
Day/Night	IR-cut filter with auto switch (ICR)
Digital noise reduction	2D/3D DNR
S/N	>52dB
IR Range	Up to 30m (98 ft) IR range
WDR	DWDR
Video	
Video Compression	Ultra 265,H.265,H.264,MJPEG
Frame Rate	Main Stream:4MP (2592*1520): Max. 20 fps; Sub Stream:720P (1280*720): Max. 30 fps; Third Stream:D1 (720x576): Max. 30 fps
HLC	Supported
BLC	Supported
OSD	Up to 4 OSDs
Privacy Mask	Up to 8 areas
ROI	Up to 2 areas
Motion Detection	Up to 4 areas
Network	
Protocols	IPv4,IGMP,ICMP,ARP,TCP,UDP,DHCP, RTP,RTSP,RTCP,DNS,DDNS,NTP,FTP,UPnP,HTTP,HTTPS,SMTP, SSL
Compatible Integration	ONVIF(Profile S), API
Interface	
Network	10/100M Base-TX Ethernet
General	
Power	12 V DC±25%, PoE (IEEE802.3 af) Power consumption: Max. 4w
Dimensions (Ø x H)	Φ118x 96 mm (Φ4.6" x 3.8")
Weight	0.35kg (0.77lb)
Working Environment	-30°C ~ +60°C (-22°F ~ 140°F), Humidity : 10%~90% RH(non-condensing)
Ingress Protection	IP67

Ordering Information

VIS-P4TXIR28LC: 4 Megapixel Turret, 2.8mm

VIS-P4TXIR4LC: 4 Megapixel Turret, 4mm



VN1A-4X4

4 Ch NVR with 4 Plug & Play Ports, 40 Mbps, 1 HD Bay

Features

- Up to 8 Megapixel Resolution Recording
- 4 Plug & Play Ports for easy camera setup PoE (Power Over Ethernet) available on all ports
- 40 Mbps Bit Rate Input
- Supports up to 4 channel simultaneous playback
- Works with ONVIF or other supported IP cameras
- Upgrade your recorder via the Cloud
- Local HDMI main monitor output with 4K Support
- Local VGA main monitor output up to 1080p
- EZ Vision Stream Connect for Networking
- Smart Analytic Support
- Multiple video search options including Smart Search for quick retrieval of footage.
- Ultra H.265/H.265/H.264 video compression
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) to manage multiple units & sites from a single platform
- Free MAC client software to easily manage your system from your Apple computer

Model	VN1A-4X4
Video/Audio Input	
IP Video Input	4-ch
Two-way Audio Input	1-ch, RCA
Network	
Incoming Bandwidth	40Mbps
Outgoing Bandwidth	64Mbps
Remote Users	128
Protocols	P2P, UPnP, NTP, DHCP, PPPoE
Video/Audio Output	
HDMI/VGA Output	HDMI: 4K (3840x2160) /30Hz, 1920x1080p /60Hz, 1920x1080p /50Hz, 1600x1200 /60Hz, 1280x1024 /60Hz, 1280x720 /60Hz, 1024x768 /60Hz, VGA: 1920x1080p /60Hz, 1920x1080p /50Hz, 1600x1200 /60Hz, 1280x1024 /60Hz, 1280x720 /60Hz, 1024x768 /60Hz
Recording Resolution	8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Audio Output	1-ch, RCA
Synchronous Playback	4-ch
Corridor Mode Screen	3/4
Decoding	
Decoding format	Ultra265/H.265/H.264
Live view/Playback	8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Capability	1 x 4K@30, 2 x 4MP@30, 4 x 1080p@30, 8 x 720p@30, 16 x D1
Hard Disk	
SATA	1 SATA interfaces
Capacity	up to 10TB for each disk
Smart	
VCA Detection	Face detection, Intrusion detection, Cross line detection, Audio detection, Defocus detection, Scene change detection, Auto tracking
VCA Search	Face search, Behavior search
Statistical Analysis	People counting
External Interface	
Network Interface	1 RJ-45 10M/100M self-adaptive Ethernet Interface
USB Interface	Rear panel 2 x USB2.0, Front panel 1 x USB2.0
Alarm In	4-ch
Alarm Out	1-ch
PoE	
Interface	4 independent 100 Mbps PoE network interfaces
Max Power	Max 30W for single port, Max 54W in total (13.5W for each)
Supported Standard	IEEE 802.3at, IEEE 802.3afk
General	
Power Supply	48V DC Power Consumption: ≤ 5 W(without HDD)
Working Environment	+14°F ~ +131°F (-10°C ~ +55°C), Humidity ≤ 90% RH (non-condensing)
Dimensions(W×D×H)	260mm ×240mm × 44mm (10.2" ×9.4" ×1.7")
Weight (without HDD)	≤ 1.12 Kg (2.47 lb)

Ordering Information

VN1A-4X4: 4 Ch NVR with 4 Plug & Play Ports
Available with 2/4/6/8/10 TB Hard Drive Options