



VN1A-16X16

16 Ch NVR with 16 Plug & Play Ports, 160 Mbps,
2 HD Bays, 4K, With Cloud Upgrade

Features

- 16 Plug & Play Ports for easy camera setup PoE (Power Over Ethernet) available on all ports
- Up to 12 Megapixel Resolution Recording
- 160 Mbs Bit Rate Input
- Supports up to 16 channel simultaneous playback
- Works with ONVIF or other supported IP cameras
- Local HDMI main monitor output with 4K Support
- Local VGA main monitor output up to 1080p
- P2P Vision Stream Connect for Networking
- Smart Analytic Support/8ch SIP Max
- Multiple video search options including Smart Search for quick retrieval of footage.
- H.265/H.264 video compression
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) to manage multiple units & sites from a single platform
- Free MAC client software to easily manage your system from your Apple computer

Model	VN1A-16X16
Video/Audio Input	
IP Video Input	16-ch
Two-way Audio Input	1-ch, RCA
Network	
Incoming Bandwidth	160Mbps
Outgoing Bandwidth	320Mbps
Remote Users	128
Protocols	P2P, UPnP, NTP, DHCP, PPPoE
Video/Audio Output	
HDMI/VGA Output	VGA: 1920x1080p /60Hz, 1920x1080p /50Hz, 1600x1200 /60Hz, 1280x1024 /60Hz, 1280x720 /60Hz, 1024x768 /60Hz HDMI: 4K (3840x2160) /60Hz, 4K (3840x2160) /30Hz, 1920x1080p /60Hz, 1920x1080p /50Hz, 1600x1200 /60Hz, 1280x1024 /60Hz, 1280x720 /60Hz, 1024x768 /60Hz
Recording Resolution	12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Audio Output	1-ch, RCA
Synchronous Playback	16-ch
Corridor Mode Screen	3/4/5/7/9/10/12/16
Decoding	
Decoding Format	Ultra 265, H.265, H.264
Live view/ Playback	12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Capability	3 x 12MP@25, 4 x 4K@30, 8 x 4MP@30, 16 x 1080P@30
Hard Disk	
SATA	2 SATA interfaces
Capacity	up to 14TB WD/Up to 18TB Seagate
Redundancy	Redundant Recording
Smart	
VCA Detection	Face detection, Intrusion detection, Cross line detection, Audio detection, Defocus detection, Scene change detection, Auto tracking
VCA Search	Face search, Behavior search
Statistical Analysis	People Counting
External Interface	
Network Interface	1 RJ-45 10M/100M/1000M self-adaptive Ethernet Interface
USB Interface	Front panel: 1 x USB2.0, Rear panel: 1 x USB3.0
Alarm In	4-ch
Alarm Out	1-ch
PoE	
Interface	16 independent 100 Mbps PoE network interfaces
Max Power	Max 30W for single port Max 240W in total (15W for each)
Supported Standard	IEEE 802.3af/at
General	
Power Supply	100 - 240 V AC Power Consumption: ≤ 20 W(without HDD)
Working Environment	+14°F ~ +131°F (-10°C ~ + 55°C), Humidity ≤ 90% RH(non-condensing)
Dimensions(W×D×H)	15" × 12.4"×1.8" (380 mm × 315mm × 46 mm)
Weight (without HDD)	≤ 5.47lb (2.48kg)

Ordering Information

VN1A-16X16: 16 Ch NVR with 16 Plug & Play Ports