


PROJECT:	Hurley Engineering Web Design Assist	UNIT TAG:	BP-1	QUANTITY:	1
REPRESENTATIVE:	Hurley Engineering Company	TYPE OF SERVICE:	Domestic Water	DATE:	_____
ENGINEER:	To Be Determined	SUBMITTED BY:	_____	DATE:	_____
CONTRACTOR:	To Be Determined	APPROVED BY:	_____	DATE:	_____
		ORDER NO.:	_____	DATE:	_____

HYDRO MULTI-B/E 2 CME10-3


Booster systems with frequency-controlled pumps





HURLEY ENGINEERING
MANUFACTURERS REPRESENTATIVES

Product photo could vary from the actual product

Conditions of Service		Pump Data		Motor Data	
Flow:	120 US gpm	Maximum operating pressure:	145 psi	Rated voltage:	208-230 V
Head:	180 ft	Liquid temperature range:	32 .. 140 °F	Main frequency:	60 Hz
Efficiency:	56.6 %	Pipe connection:	2.5NPT		
Liquid:	Water	Product number:	91149114		
Temperature:	68 °F				
NPSH required:	16.1 ft				
Viscosity:	_____				
Specific Gravity:	1.000				





Materials:

Pump: EN-GJL-200

Manifolds: EN/DIN 1.4571/ AISI 316 TI

Count	Description
1	<p>HYDRO MULTI-B/E 2 CME10-3 Product No.: 91149114 Pressure booster system designed and manufactured by Grundfos. Delivered on a common base plate, completely assembled and tested before it leaves the factory and ready for connection of water and electricity.</p> <p>All pumps are Grundfos CME pumps with integrated frequency drives connected in parallel and operated in cascade.</p> <p>The booster maintains a constant pressure through continuous adjustment of speed of the pumps and starting and stopping the pumps to meet the required flow.</p> <p>The system consists of:</p> <ul style="list-style-type: none"> -2 horizontal multistage pumps with integrated frequency converter, type CME10-3 -A suction and a discharge manifold in EN/DIN 1.4571/ AISI 316 TI -One non-return valve per pump placed on the discharge side as standard. -Two isolating valves and a clamp ring per pump for easy service and inspection of the pumps. -Pressure sensor and gauge. -CU323 Pump controller for controlling parallel coupled pumps in cascade. <p>Optional equipment:</p> <ul style="list-style-type: none"> -Redundant Primary Sensor -Water Shortage Protection -Non return valve on suction side. -Communication Modules for LON, BACnet, Modbus and GSM -Phase Failure monitoring -Beacon -Audible alarm -External transformer -High / Low Level alarm -System in operation indicating lamp -Alarm indicating lamp <p>Accessories:</p> <ul style="list-style-type: none"> -Level Switch 5 meter cable -Level Switch 10 meter cable -Extra documentation <p>Functions and features of the CU323 Pump controller:</p> <ul style="list-style-type: none"> -Constant pressure control -Automatic cascade control -Automatic alternation between pumps -Stop function -High Pressure Protection -Sensor Fault Protection -Motor Protection -Standby pumps -Automatic Display Lock -External Start / Stop (potential free contacts) -Easy to use HMI with 2 displays for set-point and process value -2 digital outputs, -Auto / manual control of pumps -Optional bus communication -Optional Safe Tank filling sequence -Optional monitoring of inlet pressure by means of inlet sensor <p>Technical data: Rated Flow: 106 US gpm</p>



Company name:

Created by:




Phone:

Date:



3/7/2019

Count	Description
	Rated Head: 191.3 ft Liquid temperature: 0 – 140 °F Max Pressure : 145 psi
	Pump Material: EN-GJL-200 Shaft Seal: AQQE (SiC/SiC/EPDM)
	Mains Supply: 208-230 V
	Starting Method CME pump: electronically Power of CME pump: 5 HP
	Size of manifold connection: 2.5NPT Net Weight: 386 lb Gross Weight: 609 lb

Description	Value
General information:	
Product name:	HYDRO MULTI-B/E 2 CME10-3
Product No.:	91149114
EAN:	5711490038651
Technical:	
Actual calculated flow:	120 US gpm
Min flow system:	15.9 US gpm
Resulting head of the pump:	180 ft
Head max:	224.7 ft
Main pump name:	CME10-3
Main pump Number:	99450818
Number of pumps:	2
Model:	A
Materials:	
Pump:	EN-GJL-200
Manifolds:	EN/DIN 1.4571/ AISI 316 TI
Installation:	
Maximum operating pressure:	145 psi
Pipe connection:	2.5NPT
Liquid:	
Pumped liquid:	Water
Liquid temperature range:	32 .. 140 °F
Liquid temperature during operation:	68 °F
Density:	62.29 lb/ft ³
Electrical data:	
Power (P2) main pump:	5 HP
Main frequency:	60 Hz
Rated voltage:	3 x 208-230 V
Starting main:	electronically
Rated current of system:	26.8 A
Controls:	
Control type:	E
Operation unit:	CU323-2
Tank:	
Diaphragm tank:	No
Others:	
Net weight:	386 lb
Gross weight:	609 lb
Product range:	NAMREG
Country of origin:	US
Custom tariff no.:	8413.70.2040



91149114 HYDRO MULTI-B/E 2 CME10-3 60 Hz



Note! All units are in [mm] unless otherwise stated.
Disclaimer: This simplified dimensional drawing does not show all details.