



JANUS
INTERNATIONAL

ADA Compliant Self Storage Doors


The ADA has stated that roll-up doors themselves do not have ADA guidelines. However, their installation and certain components may be subject to certain requirements. Janus International Series 650 and 750 doors comply with the ADA Standards for Accessible Design as defined in the Department of Justice 28 CFR Part 36, Chapter 4, as revised 9/15/10.

How many units must be ADA accessible?

- 5% if less than 200 units
- 10 units plus 2% if more than 200
- Dispersed among various sizes of spaces

External Door pull requirements:

- 48" from ground
- loop type nylon pull that a fist can fit into



Bottom bar pull requirements:

- 15"-48" from the ground when door is open
- Loop at bottom that fist can fit into



Optional Electric Operators

- *Operable parts* shall be operable with one hand and shall not require tight grasping, pinching or twisting of the wrist. The force required to activate *operable parts* shall be 5 pounds maximum




Accessibility Signage

- Must be visibly placed outside unit



Door Tensioning

- 5 lbs. maximum force as it pertains to the continuous application of force necessary to fully open a door, not the initial force needed to overcome the inertia of the door.



Contact your Janus sales manager to discuss how we can assist in your facility's ADA compliancy goals.



JANUS INTERNATIONAL
superior product + recognized value

1 866 562 2580
www.janusintl.com