

# Model 2000



Last updated: 10/10/06

## Part 1- GENERAL

### 1.01 DESCRIPTION—

- 1.01.01 Type: Continuous sheet rolling door Model 2000 as manufactured by Janus International Corporation, Temple, GA. Available in size up to 12'0" x 18'0".
- 1.01.02. Mounting: To be interior or exterior face mounted on a prepared jamb.
- 1.01.03. Related Work: Preparation of opening, miscellaneous or structural steel, iron work, access panels, master keying cylinders, finish or field painting, electrical wiring, conduit, disconnecting switches are in the scope of the work of other sections or trades.

**1.02 QUALITY ASSURANCE—** Qualifications of Manufacturer: Products utilized in this section shall be manufactured by an organization that regularly engages in the production of similar products and has a proven history of successful manufactured products acceptable to the Architect, such as Janus International Corporation.

**1.03 GUARANTEE—** All doors and components specified herein shall be guaranteed to be free of workmanship and defect for a period of 3 years.

## Part 2- PRODUCT

### 2.01 CURTAIN—

- 2.01.01 Sheets: Continuous 20" corrugated sheets roll formed from 26 gauge ASTM A653 Grade 80 full hard steel and lock seamed together.
- 2.01.02 Finish: galvanized and pre-painted with long-lasting silicone polyester paint guaranteed with a 25 year film integrity warranty to not crack, peel or blister. Additional guarantee up to 20 years against chalking and fading based on color chosen.
- 2.01.03 Bottom Bar: Roll formed clear acrylic coated galvanized steel reinforced with a 2" x 1-1/2" x 12 gauge galvanized angle that extends fully into the guides.
- 2.01.04 1-1/2" wide nylon strips attached to each edge of the back of the curtain control stretch and reduce wear.

### 2.02 WEATHERSTRIPING—

- 2.02.01 Black PVC bulb-type astragal affixed to the bottom bar assembly provides positive contact with the floor.
- 2.02.02 Polyethylene wear strip furnished on jamb leg of each guide.
- 2.02.03 (Optional) Side draft stop attaching to guide with steel angle.
- 2.02.04 (Optional) Black flexible neoprene top draft stop with 2" lip attached to curtain.
- 2.02.05 (Optional) 4" Header seal attached to header jamb.

**2.03 BARREL ASSEMBLY—** Galvanized coil steel fabricated in a 12" diameter spiral formation to enclose spring counterbalance system and provide full span curtain weight support. Attached galvanized drums are furnished with grease-filled, shielded radial ball bearings at rotating points around the axle.

**2.04 SPRING COUNTERBALANCE—** Factory lubricated, oil tempered, helical torsion springs located inside the barrel made of wire conforming to ASTM A229. Springs are attached to the steel axle tube by means of a welded spring clip. Axle tube provided is sufficient size to carry curtain load and spring torque. Spring cycle life of 15,000.

**2.05 SUPPORT BRACKETS—** Galvanized and reinforced one-piece 12 gauge formed steel brackets.

**2.06 SPRING TENSIONER—** External mounted cam action tension retaining device allows for field adjustment of spring tension on all springs.

**2.07 GUIDE ASSEMBLY—** Universal mounted guides rolled formed from 16 gauge galvanized steel and fitted with jamb leg wear strips. 2-1/4" guide depth furnished for sufficient curtain engagement. Removable galvanized door stop at top of each guide.

### 2.08 OPERATION—

- 2.08.01 Hand operated with #6 Angola rope on size up to 10'0 x 10'0" attaching to the bottom bar assembly.
- 2.08.02 Universal 5.7:1 cast iron reduced drive hand operated chain hoist furnished for all doors over 10'0" wide or 10'0" tall.
- 2.08.03 (Optional) Electric operator (furnished by vendor) with electric 72 tooth sprocket operator kit for door adaptation.

**2.09 LOCKING MECHANISM—** Dual steel bottom bar slide locks suitable for pad locks (provided by others) mount to the inside angle of the bottom bar. Chain keeper guide mounted to wall for chain operation doors.

**2.10 HOOD (Optional) —** Fabricated from 20 gauge steel and reinforced with end caps and roll formed edges. Manufactured square.

**2.11 FINISH—** Non-galvanized surfaces, excluding axle tube, to consist of shop coat of rust inhibitor primer.

## Part 3- EXECUTION

**3.01 INSTALLATION—** To be performed by an authorized Janus International Corporation representative or professional door installer in accordance with the Janus installation standards, instructions and recommendations.

### HEAD ROOM REQUIREMENTS

Opening Height	Vertical Headroom	Horizontal Headroom
Thru 8'0"	17"	19"
Over 8'0" thru 10'0"	19"	21"
Over 10'0" thru 14'0"	20"	22"
Over 14'0" thru 16'0"	21"	23"
Over 16'0" thru 18'0"	22"	24"

### SIDE ROOM REQUIREMENTS

Operation	Guide	Outside of Bracket Tensioner End	Outside of Bracket Drive End	Outside of Hand Chain Drive	Each End of Axle
Push Up	2-1/2"	4-1/2"	4-1/2"	---	7"
Reduced Drive Chain	2-1/2"	4-1/2"	5-1/4"	8-1/4"	7"
**Electric	2-1/2"	4-1/2"	5-1/4"	---	7"

\*Vertical head room: the space above the clear opening on the same face of wall (header).

\*Horizontal head room: the amount of space required off of the wall to which the door is fastened.

\*Side room: the amount of space required on each side away from the opening along the face of the wall.

\*\*Excludes electric operator.