

Wave Plus

Smart Indoor Air Quality Monitor with Radon Detection

DOWNLOADS



We spend 90% of our time indoors. Measuring our Indoor Air Quality (IAQ) is one of the most important steps we can take in preventing illness and increasing productivity, energy and good health. Airthings, the IAQ specialists and experts in Radon, created the Airthings Wave Plus-the first smart IAQ monitor with Radon detection, designed for homes and all populated spaces. It is the perfect solution for homeowners, employers and facility managers to gain full visibility into six indoor air factors; Radon, carbon dioxide (CO₂), airborne chemicals (TVOCs), humidity, temperature and air pressure. Airthings Wave Plus includes a free app (iOS/Android) and an online dashboard with advanced analytics options.

AIRTHINGS DASHBOARD

Continuous monitoring of your Indoor Air Quality is necessary to minimize potential health effects. The Airthings App and online dashboard provide a quick and easy solution to view, compare and export data for your particular needs. Users have complete access to interpretations of IAQ data and tips to reduce indoor air hazards, optimize ventilation and save energy.

PRODUCT FEATURES

Sensors: Radon, CO₂, VOC, Temp, Humidity & Air Pressure Visual indicator: Red/Yellow/Green glow ring Long battery life: Bluetooth: 16 months SmartLink (Hub): 18 months Future low power mode: TBD months

Supports wall or ceiling mount Free mobile app for iOS and Android Web dashboard Mobile notifications Wireless connection (Bluetooth or Airthings SmartLink)

ADDITIONAL SPECIFICATIONS

Operational Environment: 39°F to 104°F Weight: 7.7 oz (with batteries) Dimensions: 4.7in (diameter) x 1.4in (height) Power: 2 AA batteries Connectivity: Bluetooth & Airthings SmartLink

ADDITIONAL INFORMATION

PACKAGE CONTENTS

Air Quality Detector 2 AA batteries Instruction Manual Mounting screw

PRODUCT CODES EAN: 7090031109301 SKU: 2910 MODEL: 2930

TVOC

EASY INSTALLATION WITH APP

To install the Wave Plus simply download the Airthings App, pull the battery tab, mount it to the wall or ceiling, and follow the easy instructions in the app to register your device. In addition, simply wave in front of the device to receive a color-coded visual indicator of the overall air quality.

IAQ SENSOR SPECIFICATIONS

Sensor sampling interval: 5 minutes Works with Sensor resolution: IFTTT Temperature ∓ 0.1°F Humidity ∓1% Pressure ∓0.15hPa Settling time: TVOC ~7 days CO, ~7 days CO₂ details App Store NDIR Sensor (Non-Dispersive Infra-Red) Measurement range 400–5000 ppm Non condensing 0 – 85%RH Optimum Accuracy ± 30 ppm $\pm 3\%$ within 60 - 95°F and 0 – 80%RH can be reached after multiple settling cycles on locations with natural indoor CO₂ fluctuations

RADON SPECIFICATIONS

Radon sampling: Passive diffusion chamber Detection method: Alpha spectrometry Sampling interval: 1 hour Measurement range: 0 – 500 pCi/L Accuracy/precision at 5 pCi/L: After 7 days: ~10 % After 2 months: ~ 5 %

REQUIREMENTS

iOS 10 or newer / Android 6 or newer, supporting Bluetooth 4.2 or later

PACKAGE

Weight: 12.2 oz Dimension: 6x6x1.8 inches













