

Models	CLC pro 300	CLC pro 300	CLC pro 400	CLC pro 450	CLC pro 500
Number of tines CLC pro	10	12	13	15	17
Number of tines CLC pro Classic	10	12	13	15	17
Number of tines CLC pro Cut	7	9	11	13	-
Working width (m)	3,00	3,50	4,00	4,50	5,00
Transport width (m)	3,00	3,50	2,85		
Row spacing (mm)	810				
Frame box section (mm)	100x100		Central 200x200 - External 100x100		
Linkage	Cat II & II		Cat III & IV		
Underbeam clearance (mm)	870				
Average tine spacing (mm) CLC pro	280	280	290	290	290
Average tine spacing (mm) CLC pro	280	280	290	290	290
Average tine spacing (mm) CLC pro	420	385	350	350	
Min/Max HP CLC pro	120/240	135/270	185/300	190/325	200/350
Weight (Kg) CLC pro Claasic SB* + levelling tine + Actiring	1420	1640	2400	2770	2960
Lifting capacity (t) CLC pro Classic SB* + Levelling tine + Actiring**	3,9	4,3	5,9	6,8	7,3

AR\* = Auto-Reset / SB\* = Shear Bolt

\*\* Consider -15% if cage roller/ equal for Actiflex/+15% for Actipack or double disc gang