

	Kverneland Rau iXter A		
Mounted sprayer models	A8	A10	A12
1. Tank size			
Nominal / maximum main tank capacity	800 l / 965 l	1000 l / 1185 l	1200 l / 1395 l
Clean water tank / Hand wash tank	130 l / 18 l	130 l / 18 l	130 l / 18 l
Chemical inductor with opening of 40x40 cm	30 l	30 l	30 l
2. Empty weight (total machine incl. boom)			
... with HOSA 12 m	889 kg	901 kg	913 kg
... with HOSA 15 m	952 kg	964 kg	978 kg
... with HC 18 m	1207 kg	1219 kg	1231 kg
... with HC 20 m	1287 kg	1299 kg	1311 kg
... with HC 21 m	1293 kg	1305 kg	1317 kg
3. Measurements			
Width (total machine incl. boom)	HOSA = 2,35 m / HC = 2,50 m		
Height (total machine incl. boom)	HOSA12 = 2,56 m / HOSA15 = 2,85 m / HC = 3,30 m		
Length (total machine incl. boom)	HOSA = 1,35 m / HC18 m = 1,45 m / HC20-21 m = 1,65 m		
4. Pumps			
Piston-diaphragm pumps	100, 150, 200 l/min		
5. Electronics			
5.1. Remote control			
EC 5-section 3-way-valves, for pre-selection hydr. (incl. EC control box)	▲* not for HC		
5.2. Basic spray computer			
FMC 5-section 2-way-valves, for pre-selection hydraulics (incl. FMC control box)	▲ ²		
FMC 7-section 2-way-valves, for pre-selection hydraulics (incl. FMC control box)	▲ ²		
FMC 9-section 2-way-valves, for pre-selection hydraulics (incl. FMC control box)	▲ ⁴		
FMC 5-section 2-way-valves, for oilcircuit hydraulics (incl. FMC control box)	▲ ²		
FMC 7-section 2-way-valves, for oilcircuit hydraulics (incl. FMC control box)	▲ ⁴		
FMC 9-section 2-way-valves, for oilcircuit hydraulics (incl. FMC control box)	▲*		
6. Other basics			
Chemical inductor	▲		
PTO shaft 6-splines	▲		
Frame stand, Clean water tank, Hand wash tank, Manometer, Mechanical level indicator, Tank inside cleaner, Drain (via filter)	standard		
7. Accessories (also loose available)			
Protection curtain	●		
Hydrant filling connection 2"	●		
GEKA filling adapter 1" for hydrant filling	●		
Filling hose 8m 1,5" (for sucking from external)	●		
Camlock adapter 1,5" to 2" for filling hose	●		
Float for filling hose	●		
Non return valve 1,5" for filling hose	●		
Urea sieve	●		
Pump out connection	●		
Parking frame	●		
Battery cable 3 pin (only for EC/FMC, if no power connector at tractor)	●		
Starguide IV	●		

Booms	HOSA	HC
Type	12 / 15	18 / 20 / 21
1. Basic boom functionality		
Working width (m)	12 / 15	18 / 20 / 21
Material	Aluminium	Steel
Transport position	Vertical	Vertical
Folding drive	Hydraulically	Hydraulically
2. Spray sections		
Standard	5 / 5	5 / 7 / 7
Alternative 1 (two sections more than standard)	7 / 7	7 / 9 / 9
Alternative 2 (two sections less than standard)	- / -	- / 5 / 5
3. Spray jets		
Monojets	▲ ¹	▲ ¹
Trijets	▲ ²	▲ ²
Pentajets		▲ ²
4. Other		
Road lights	●	●
Electrical or manual border nozzle	●	●
Electrical or manual verge nozzle	●	●
▲* - ▲*** - = one of these choices must be selected, ▲ = must be selected, ● = option, free to select		