

Presentation of the machine

Technical specifications

Characteristics	Fixed models				
Working width (m/ft)	2.00 (6'6")	2.50 (8'2")	3.00 (9'10")	3.50 (11'6")	4.00 (13'1")
Transportation width (m/ft)	2.00 (6'6")	2.50 (8'2")	3.00 (9'10")	3.50 (11'6")	4.00 (13'1")
Number of discs	16	20	24	28	32
Dimension of discs (mm)	Conical, notched Diam. 520 (20 1/2") thickness 5 mm (3/16") standard Diam. 520 (20 1/2") thickness 5 mm (3/16") large notches on option				
Gap between discs (mm)	245 mm (9 3/4")				
Type of safety device	Disc mounted on independent arm with elastomer safety device, diam. 34 mm				
Disc hub	Angular contact ball bearing with 5-lip seal				
Depth control	Mechanical or hydraulic roller adjustment using plastic chocks				
Working depth	From 2 cm (1") to 10 cm (3 7/8")				
Available rollers	Cage roller D550 mm (22 1/2") / Actiflex roller D580 mm (23 1/2") Double cage roller D400 mm (15 3/4") Actiring D540 mm (21 1/4") / Actipack D560 mm (21 1/4")				
Min./max. power	50/100 hp (37/75 kW)	60/120 hp (45/89 kW)	75/150 hp (56/112 kW)	90/180 hp (67/134 kW)	110/200 hp (82/149 kW)
Speed range in use	From 8 to 20 km/h (from 5 to 12 mph)				
Light signal kit	Option				
Couple category (upper link)	Cat II / III				
Coupling category (on lifting arm)	Cat II / III				
Weight with all options and Actipack roller (approximate weight for the heaviest machine)	1,450 kg (3,196 lbs)	1,680 kg (3,704 lbs)	1,920 kg (4,233 lbs)	2,240 kg (4,938 lbs)	2,580 kg (5,688 lbs)

Characteristics	Folding models		
Working width (m/ft)	4.00 (13'1")	5.00 (16'5")	6.00 (19'8")
Transportation width (m/ft)	2.45 (8'3")		
Number of discs	32	40	48
Dimension of discs (mm)	Conical, notched Diam. 520 (20 1/2") thickness 5 mm (3/16") standard Diam. 520 (20 1/2") thickness 5 mm (3/16") large notches on option		
Gap between discs (mm)	250 mm (9 3/4")		
Type of safety device	Disc mounted on independent arm with elastomer safety device, diam. 34 mm		
Disc hub	Angular contact ball bearing with 5-lip seal		
Depth control	Mechanical or hydraulic roller adjustment using plastic chocks		
Working depth	From 2 cm (1") to 10 cm (3 7/8")		
Available rollers	Cage roller D550 mm (22 1/2") / Actiflex roller D580 mm (23 5/8") Double cage roller D400 mm (15 3/4") Actiring D540 mm (21 1/4") / Actipack D560 mm (21 1/4")		
Min./max. power	110/200 hp (82/149 kW)	130/250 hp (97/186 kW)	150/300 hp (112/223 kW)
Speed range in use	From 8 to 20 km/h (from 5 to 12 mph)		
Light signal kit	Option		
Couple category (upper link)	Cat III		
Coupling category (on lifting arm)	Cat III		
Weight with all options and Actipack roller (approximate weight for the heaviest machine)	3,010 kg (6,636 lbs)	3,560 kg (7,848 lbs)	4,150 kg (9,149 lbs)