

# Presentation of the machine

## Technical specifications

### Fixed models

Characteristics	Fixed models			
Working width (m)	2.50 (8'2")	3.00 (9'10")	3.50 (11'6")	4.00 (13'1")
Transportation width (m)	2.50 (8'2")	3.00 (9'10")	3.50 (11'6")	4.00 (13'1")
Number of discs	20	24	28	32
Dimension of discs (mm)	Conical, notched, with a diameter of 600 (23 5/8") and 6 mm (1/4") thickness, either standard or with a large notch as an option.			
Gap between discs (mm)	245 mm (9 3/4")			
Type of safety device	Disc installed on independent arm with safety by elastomer diam. 40			
Disc hub	Angular contact ball bearing with 5-lip seal			
Depth control	By the roller with hydraulic adjustment by means of plastic chocks or manual adjustment by plastic chocks			
Working depth (cm)	From 2 cm (1") to 15 cm (6")			
Available rollers	Cage roller D550 mm (22 1/2") / Actiflex roller D580 mm (23 5/8") Double cage roller D400 mm (15 3/4") Actiring D540 mm (21 1/4") / Actipack D560 mm (21 1/4")			
Min./max. power	70 / 180 hp (52/134 kW)	90 / 200 hp (66/147 kW)	110 / 220 hp (81/162 kW)	130 / 240 hp (96/176 kW)
Speed range in use	From 8 to 20 km/h (from 5 to 12 mph)			
Light signal kit	Option			
Coupling category (upper link)	Cat II / III			
Coupling category (on lifting arm)	Cat II / III			
Weight with all options and Actipack roller (approximate weight for the heaviest machine)	1,980 kg (4,365 lbs)	2,250 kg (4,960 lbs)	2,500 kg (5,512 lbs)	2,850 kg (6,283 lbs)