

Turbo and Turbo F

Technical Data

| Models | Turbo 3000 | Turbo 3500 | Turbo 4000F | Turbo 5000F | Turbo 6000F |
|------------------------------------|---|------------|-------------|-------------|-------------|
| Number of tines | 15 | 17 | 21 | 27 | 31 |
| Working width (m) | 2,82 | 3,19 | 3,94 | 5,07 | 5,81 |
| Roller width (m) | 3,00 | 3,50 | 4,50 | 5,50 | 6,00 |
| Number of tine rows | 4 | 4 | 4 | 4 | 4 |
| Transport width (m) | 3,00 | 3,50 | 2,90 | 2,90 | 2,90 |
| Tine models | Reflex tine (S-tine) or C-Tine | | | | |
| Row spacing (mm) | From 510 mm to 900mm | | | | |
| Frame box section (mm) | 100x100 | | | | |
| Linkage | Cat II & III | | | | |
| Underbeam clearance (mm) | 725 | | | | |
| Regular tine spacing (mm) | 19 | | | | |
| Depth adjustment | Hydraulic by spacers | | | | |
| Levelling device | Levelling tines or hollow discs | | | | |
| Roller offering | Cage roller, double cage roller, Actiring, Actiflex, Actipack | | | | |
| Min/Max HP | 80/150 | 100/175 | 120/200 | 150/250 | 180/300 |
| Total weight with Cage roller (kg) | 1325 | 1460 | 2565 | 2955 | 3215 |
| Total weight with Actiflex (kg) | 1540 | 1715 | 2863 | 3295 | 3645 |
| Total weight with Actipack (kg) | 1720 | 1915 | 3129 | 3506 | 3981 |