

Model	u-drill rigid		u-drill fold		u-drill plus	
Working width (m)	3.0	4.0	6.0	3.0	4.0	6.0
Transport width (m)	3.0	4.0	3.0	3.0	4.0	3.0
No. of CD coulters	24	32	48	24	32	48
No. of metering devices	1	1	2	2	2	2
Hopper capacity (l)	3,000		4,350	3,000		4,350
Required oil volume	> 90l/min					
Single-acting hydr. valve + zero-pressure return for fan drive	●	●	●	●	●	●
1 x double-acting hydraulic valve for machine control	●	●	●	●	●	●
Power requirement 12 V > 70 A	●	●	●	●	●	●
CD double disc coulters	●	●	●	●	●	●
Coulter pressure up to 100kg	●	●	●	●	●	●
Electro-hydraulic adjustment of the placement depth via ISOBUS terminal	●	●	○	●	●	●
Press wheels (Ø 380 x 50mm)	●	●	●	●	●	●
Row spacing (12.5cm)	●	●	●	●	●	●
Coulter staggering 17.5cm	●	●	●	●	●	●
Electronic adjustment of the seed quantity with radar	●	●	●	●	●	●
Filling level sensors in the seed hopper	●(1)	●(1)	●(2)	●(2)	●(2)	●(2)
Fan speed sensor	●	●	●	●	●	●
Metering device monitoring	●	●	●	●	●	●
Electronic half-width shut-off	-	-	●	●	●	●
Mid-mounted front packer (Ø 800mm)	○	○	○	○	○	○
Complete front packer (Ø 800mm)	-	○	○	-	○	○
Electro-hydraulic adjustment of the disc harrow working depth via ISOBUS terminal	●	●	●	●	●	●
Disc harrow (Ø 460mm)	●	●	●	●	●	●
Offset tyre packer (Ø 900mm)	●	●	●	●	●	●
Maintenance platform, road transport lights, in-hopper light	●	●	●	●	●	●

Hydraulic fan drive	●	●	●	●	●	●
Lower link suspension Cat. 3N (825mm)	●	●	○	●	●	○
Lower link suspension Cat. 3 (965mm)	○	○	●	○	○	●
Lower link suspension Cat. 4 (965mm)	-	-	○	-	-	○
S-shaped seed harrow 10mm	●	●	●	●	●	●
Finger harrow 12mm	○	○	○	○	○	○
Calibration set	●	●	●	●	●	●
Filling auger	-	-	○	-	-	-
Hydraulically folding track marker with notched discs	○	○	○	○	○	○
Track eradicators (2 tines per track)	○	○	○	○	○	○
Pneumatic brakes	○	○	○	○	○	○
Hydraulic brakes	○	○	○	○	○	○
Extended drawbar for tractors with twin tires up to 4.5m	○	○	○	○	○	○
Pre-emergence marker (centre marking)	○	○	○	○	○	○
LED work lights	○	○	○	○	○	○
iM Tellus for non-ISOBUS-capable tractors	○	○	○	○	○	○
iM Tellus for ISOBUS tractors	○	○	○	○	○	○
Hopper volume weighing system with separate monitor	○	○	○	-	-	-
Headland management	●	●	●	●	●	●
Weight (kg) (with front packer + track eradicators)	4,600	5,400	8,120	4,800	5,600	8,400
Min. power requirement (kW)	90		120	130		

● Standard equipment ○ Option

The statements in this leaflet are intended as general information and for global distribution. Kvemeland Group does not accept any liability for any inaccuracies, errors or omissions. Not all models, specifications and options may be available in all countries. For more information, please contact your local dealer. Kvemeland Group reserves the right to make changes in the design and/or the specifications shown or described in this leaflet at any time. Individual features may be added or removed without prior announcement or obligations. If any safeguards of the machine have been removed on the pictures, this was solely done for a better visibility of the machine functions. To prevent any risk of injury, safeguards should never be removed. If, for instance for maintenance purposes, a safeguard needs to be removed, please contact our after sales service.

© Kvemeland Group Soest GmbH.