

# R4000 PRODUCT SPECIFICATION GUIDE

Part Number	BCI Group Size	Capacity @ 25°C (77°F)						Energy (Wh @C100)	Dimensions inches (mm)			Weight lbs (kg)	Terminal Type	Case Material
		AH @C5	AH @C20	AH @C100	Min @25A	Min @56A	Min @75A		Length	Width	Height			

## 6V

REV-GC2-225	GC2	185	225	239	475	-	124	1434	10.24 (260)	7.1 (180)	10.8 (274)	66.2 (30)	DT	PP
REV-305-335	902	275	335	355	750	-	208	2130	11.6 (295)	7.1 (180)	14.4 (366)	104.7 (47.5)	DT	PP
REV-L16-400	903	331	400	424	915	-	270	2544	11.6 (295)	7.1 (180)	16.9 (428)	119.5 (54.2)	DT	PP

## 8V

REV-GC8-170	GC8	144	170	180	361	115	75	1440	10.24 (260)	7.1 (180)	10.8 (274)	70.6 (32)	DT	PP
-------------	-----	-----	-----	-----	-----	-----	----	------	-------------	-----------	------------	-----------	----	----

## 12V

REV-24-85	24	73	85	88	165	-	42	1056	10.24 (260)	6.6 (168)	8.4 (214)	49.2 (22.3)	M8	ABS
REV-27-105	27	89	105	110	204	-	50	1320	12.1 (306)	6.6 (168)	8.4 (214)	59.8 (27.1)	M8	ABS
REV-31-115	31	97	115	119	242	-	65	1428	13.0 (330)	6.8 (173)	8.7 (220)	67.5 (30.6)	DT	ABS
REV-GC12-150	GC12	128	150	159	310	119	86	1908	12.9 (327)	7.1 (180)	10.8 (274)	91.5 (41.5)	M8	ABS
REV-185-250	921	210	250	265	530	-	170	3180	15.2 (387)	7.1 (180)	14.5 (368)	147.7 (67)	DT	PP
REV-4D-240	4D	200	240	254	560	-	155	3048	20.8 (528)	8.7 (222)	9.8 (250)	142.4 (64.6)	DT	PP
REV-8D-260	8D	215	260	276	610	-	168	3312	20.6 (522)	10.6 (268)	8.9 (226)	160 (72.5)	M8	ABS
REV-8D-330	8D	260	330	350	740	-	210	4200	20.8 (528)	11.1 (282)	9.8 (250)	182.8 (82.9)	DT	PP

A. The amount of capacity the battery can deliver when discharged at a constant rate at 77°F (25°C) to a voltage of 1.75V/cell.

