



Standard Canister Storage

Stratasys does NOT include an expiration date on its thermoplastic materials. Our prior guidance of “best used within 3-years from the manufacturing date” has been deemed unnecessary as thermoplastics typically do not degrade over time unless exposed to high temperatures, UV, ozone, or other adverse environmental conditions.

To maintain the material in its optimal condition, Stratasys recommends that the material be stored in its original packaging in a cool (65 – 75 °F), dry environment (<50% RH). Canisters, cartridges, and spools should be sealed in its mylar bag before use. After the packaging is opened, it should either stay loaded in the machine with the air-dryer system constantly purging moisture from the filament lines, or the product should be re-sealed, returned to its original packaging and stored in a cool, dry environment.

If material cannot be stored under optimal conditions (see ranges above) it is recommended that a moisture test be performed, and drying process implemented to ensure that the moisture level is below 0.04% moisture prior to printing.

At Stratasys, we are committed to ensuring the quality and consistency of your material supply. If you have questions regarding the changes noted above, please contact your local reseller or a Stratasys Technical Support Specialist.

Stratasys Headquarters

7665 Commerce Way,
Eden Prairie, MN 55344
+1 800 801 6491 (US Toll Free)
+1 952 937-3000 (Intl)
+1 952 937-0070 (Fax)

1 Holtzman St., Science Park,
PO Box 2496
Rehovot 76124, Israel
+972 74 745 4000
+972 74 745 5000 (Fax)

stratasys.com
ISO 9001:2008 Certified



© 2019 Stratasys Ltd. All rights reserved. Stratasys and Stratasys signet are trademarks or registered trademarks of Stratasys Ltd. and/or its subsidiaries or affiliates and may be registered in certain jurisdictions. All other trademarks belong to their respective owners. Product specifications subject to change without notice. Printed in the USA.
BP_FDM_CanisterStorage_0119b