



In your business, payroll accuracy is paramount. And a dependable, durable time and attendance terminal can help you deliver the accurate employee time and attendance information that your customers are looking for. Deliver a complete solution to your customers: your software, coupled with an Accu-Time Systems PeoplePoint Plus terminal.

The PeoplePoint Plus™ time and attendance terminal delivers rich graphics and video content on a 7" display. Along with our long list of standard features, the PeoplePoint allows for additional features such as high-volume speakers, a camera with a wide view angle, and a powerful processor that allows users to efficiently interact with the device.

The PeoplePoint Plus time clock is focused on addressing the growing customer challenges of tracking employee data, adhering to compliance by giving employees greater self-service options, and meeting those challenges with products, services, and resources unmatched in quality and functionality.

PeoplePoint Plus™ features include:

- 7" Widescreen Touch Display
- High performance processor/Single Core Processor
- eMMC- 8 GB Storage
- Optional- Biometric Suprema or Lumidigm reader
- Supports Linux
- Programming Languages Include: Java, Python, C/C++
- Optional WiFi 802.11 a,b,g,n
- DHCP & Static IP
- Optional speakers with max volume, up to 80db at 40" (1 meter) distance
- Optional wide angle camera. Sensitivity range: from 125 lx to 50000 lux; Resolution 800x480
- Optional microphone



PeoplePoint Premium™ Terminal Specifications

DISPLAY	7" TFT Capacitive Touch, 16:9.6 Aspect Ratio, 800 x 480 Resolution
PROCESSOR	Freescale i.MX6 up to 1GHz (Single Core)
MEMORY	1GB DDR3 RAM 512MB NAND FLASH
MASS STORAGE	Non-removable eMMC 8GB, of which 2.5GB are user available
CLOCK	Battery-backed real-time clock, 12- or 24-hour format (quartz precision)
KEYPAD	20-key tactile, 4x5 matrix - Numeric keypad 0-9 - Eight software definable function keys - Clear/Enter keys Customizable overlay allows for unique graphic options
PROGRAMMING	- Linux OS standard. One active, one inactive OS, providing for fault tolerant upgrade capabilities - C/C++, Java™/Python - Web services - HTML capable - Software Development Kit (SDK)
APPLICATION SOFTWARE	ATS AccuCollect - Configurable punch workflow management including job transfers, attestations, and more.
DIAGNOSTICS	On-board and remote diagnostics capability
INTERFACE	- Standard 10/100/1000 BASE-T Ethernet - Optional Wi-Fi with WPA support - Optional internal 3G cellular modem - Internal USB port
ENCLOSURE	PC/ABS
POWER	- 12 VDC (nominal) 1A, 12W maximum under normal operation - Optional uninterruptible power supply - Optional IEEE 802.3af/compliant POE
ENVIRONMENT	- Operation Temperature: 0° to 50°C (32° to +122°F) - Storage Temperature: -20° to 80°C (-4° to +176°F)
DIMENSIONS	H 26.67cm x W 22.86cm x D 10.16cm (H 10.5" x W 9" x D 4")
CERTIFICATIONS	CE Mark, FCC Part 15 Class A
ACCESSORIES	- Biometric readers – 1:1 and 1:n - Integrated visible or infrared barcode readers - Integrated magnetic stripe readers - Contactless smartcard readers (HID® Prox, Mifare™, iClass®, Marin) - External readers - Wiegand compatible - Dry contact low voltage relay modules dual Form C - Uninterruptible power supply

ACCU-TIME SYSTEMS INC.

THE AMERICAS

Corporate Headquarters
420 Somers Road
Ellington, CT 06029
TEL: 1 (860) 870-5000
FAX: 1 (860) 872-1511
Toll Free: 1 (800) 355-4648
sales@accu-time.com
www.accu-time.com

EMEA & APAC

United Kingdom
TEL: + 44 (0) 1202 606068
sales@accu-time.com

All Other Locations

TEL: +44 (0) 2920 885599
sales@accu-time.com

