

SPECIFICATIONS



COMMUNICATIONS

- **Maximum RF range:** Up to 400 m (1,312 ft.) – open air
- **Protocols:** Proprietary bi-directional radio protocol
- **Modulation and frequency:** FSK modulation:
 - 869.225 MHz (Europe)
 - 868.3 MHz (China)
 - 916.5 MHz (North America and Australia)
 - 916.3 MHz (Israel)
- **Data security:** 32-bit ID, over 4 billion combinations

POWER

- **Battery:** Two C 1.5 V alkaline batteries
- **Battery life:** Up to 5 years

DIMENSIONS

- **Size (H x W x D):** 95 x 95 x 42 mm (3.74 x 3.74 x 1.65 in.)
- **Weight:** 300 g (0.66 lb.) not including batteries and accessories
- **Pull cord length:** 63.5 cm including the plastic grip

ENVIRONMENT

- **Operating ambient temperature range:** -10°C - 55°C (14°F - 131°F)
- **Storage ambient temperature range:** -20°C - 70°C (-4°F - 158°F)
- **Operating humidity:** up to 93% non-condensing
- **Water and dust resistant:** IP54 compliant

CERTIFICATIONS and APPROVALS

- FCC, IC
- CE
- SRRC
- AS4607
- EN50134
- UL1637

PART NUMBER: ES700SPD