

40' Open Top Container

Open top containers are especially suitable for transporting overheight cargo, i.e. cargo taller than 2.54m (8'5"). They are available in two sizes: 20' and 40'.



Cargo can be loaded by crane from the top-side. Overheight cargo can also be loaded from the door-side since the door header can be swung open.

Numerous lashing rings are available on the four corner posts, top-side rails and bottom-side rails for securing the cargo. If the cargo needs to be protected from rain, tarpaulin sheets can be provided to cover the top of the container.

Commodities commonly shipped in the open top container include machinery, industrial boilers, tractors, steel pipes, steel bars and cables.

Description	Metric	U.S.
Cubic Capacity	65.5 cubic meters	2,306 cubic feet
Max Payload	26,580 kg	58,602 lb
Tare Weight	3,900 kg	8,598 lb
Max Gross Weight	30,480 kg	67,200 lb
Internal Length	12.040 m	39'6"
Internal Width	2.350 m	7'8"
Internal Height	2.310 m	7'7"
Door Opening Width	2.340 m	7'8"
Door Opening Height	2.260 m	7'5"
Roof Opening Length	11.600 m	38'1"
Roof Opening Width	2.140 m	7'0"

Disclaimer: Please note that in certain exceptional cases, the containers operated by various steamship lines may have specifications that differ from the descriptions above. Also, cargo in container must conform to the dimensional regulations and laws stipulated by the host country, thus payload capacity may be affected.

Final max payload is subject to Rail, DOT and individual State weight regulations.

I.C.E. Transport Co., Inc.

219 South St. Suite 100 * New Providence, NJ 07974

Telephone: (732) 516-9555
(800) 241-1423

Fax: (732) 516-9777

E-Mail: ice@icetransport.com