

Application

Widely used in the residential and shutter applications.

To cover any width of opening, any number of doors can be used.

To accommodate different building designs, doors can slide to one or both sides.

Where doors are fitted externally, a canopy is recommended.

Door Specification

Track System:

For Individual Doors:

Max Door Height

Max Door Weight Nylon Tyre Hanger

Door Thickness

Single Run 80

3000mm

80kg

28-48mm

For ease of operation it is recommended that the door width should not exceed 75% of door height.

Timber doors for interior use can be of flush construction or glazed.

Timber doors for industrial applications should be framed, ledged and braced.

Metal doors should be constructed of box section, channel or angle framing, well braced and clad with flat or corrugated sheets.

Standard Sets and Packs

Sets comprise of top track, hangers, doors stops, nylon guides, screws and instructions.

Set No.	Max. Door Width	Track Length
SR80-20/1	950mm	2000mm
SR80-30/1	1450mm	3000mm
Pack No. SR80-1PK	Fitting pack only no track.	

Hardware Specification

Track:	80A
Material	Aluminium
Finish	Mill or clear anodised
Standard Lengths	2000mm, 3000mm, 4000mm and 6000mm

Brackets:	91
Face fitted stainless steel, angle	5SS/120
Double face fitted bracket SS	
Fit at 600mm maximum centres	

Hangers (2 per door):

Hangers:		Full Stainless
Timber doors - plate (surface)	57ENP	57SS/ENP
All hangers suffixed 'N' have nylon tyre wheels and are fitted with ball race bearings.		
Nylon tyre wheel hangers should not be used on installations involving temperatures exceeding 80°C.		

Guides:	
Timber doors - SS plate fitting	106E/94
Timber doors - nylon guide	101N
Multiple doors	102W/94SS

Channels:	
Aluminium	94A Aluminium
	94PPA Aluminium support & Polypropylene
Finish	Aluminium - Mill or Clear Anodised
Standard lengths	2000mm, 3000mm, 4000mm and 6000mm

Brass	94B
Standard Lengths	2000mm, 3000mm, 4000mm and 6000mm

Accessories:	
Flush pulls	401
Door stop	120DS
Locks	6400 Series Sliding mortice locks
Flush Bolts	456
Flush bolts and flush pulls are available in (PVD) PVD Brass, (SN) Satin Nickel & (PN) Polished Nickel	



