

**SAVINGS YOU CAN SEE!
BEST VALUE: MAXIMUM STRENGTH & ENERGY EFFICIENCY**

FEATURES & BENEFITS:

- **Nearly impenetrable barrier to air & water penetration:**
Fusion welded 3 ¼" frame & sash provide strength, stability, and rigidity
- **More traditional wood appearance on exterior:**
Unique cove mold design
- **Maximized water runoff, even in driving rain:**
Weeped saddleback sill system
- **Resists air infiltration:** Deeply pocketed head with weather stripping
- **Better thermal barrier than most other windows:**
.070" walls are a full 12% thicker than most other windows
- **Smooth and Maintenance free operation:** Coil pack balancers
- **Easy sash operation:** Attractive, integral lift rail
- **Easy to clean:** Tilt sash
- **Lifetime warranty on all vinyl frames**
- **Made in the USA Certified®**



SPECIFICATIONS:

Maximum Size	Fin: 54" x 77"
Maximum Size	Flange: 54" x 77"
Design Pressure	+70/-85 PSF
Muntin	Grids Between Glass (GBG) or Simulated Divided Light (SDL)
Grid Options	Colonial, Prairie, Perimeter
Frame Depth	3 ¼"
Frame Style	Fin & Flange
Colors	White, Desert Sand, or Bronze Exterior/White Interior
Approvals/ Certifications	HVHZ, Good Housekeeping Seal, Earthwise, NFRC, Energy Star, Made in the USA Certified®, Florida State Product Approval



earthwise
WINDOWS & DOORS



SINGLE HUNG VINYL WINDOW

THE PROTECTION & APPEARANCE YOU'RE SEEKING

FEATURES & BENEFITS:

- **Nearly impenetrable barrier to air & water penetration:**
Fusion welded 3 ¼" frame & sash provide strength, stability, and rigidity
- **More traditional wood appearance on exterior:**
Unique cove mold design
- **Maximized water runoff, even in driving rain:**
5 degree sloped sill
- **Resists air infiltration:** Deeply pocketed head with weather stripping
- **Better thermal barrier than most other windows:**
.070" walls are a full 12% thicker than most other windows
- **Smooth and maintenance-free operation:** Coil pack balancers
- **Easy sash operation:** Attractive, integral lift rail
- **Easy to clean:** Tilt sash
- **Lifetime warranty on all vinyl frames**



SPECIFICATIONS:

Maximum Size	Fin: 48" x 72"
Maximum Size	Flange: 53 ⅛" x 72"
Design Pressure	±50 PSF
Glass	Insulated, Impact Insulated
Muntin	Grids Between Glass (GBG) or Simulated Divided Light (SDL)
Grid Options	Colonial, Prairie, Perimeter
Frame Depth	3 ¼"
Colors	White, Desert Sand, or Bronze Exterior/White Interior
Approvals/ Certifications	Earthwise, Good Housekeeping Seal, Energy Star, NFRC, Made in the USA Certified®, Florida State Product Approval



SINGLE HUNG IMPACT ALUMINUM WINDOW

MAXIMIZE PROTECTION AGAINST WATER AND WIND-BORNE DEBRIS — AT A GREAT VALUE



FEATURES & BENEFITS:

- **Superior Strength and Durability:**
3¼" frame depth
- **Maximize prevention of air and water penetration:** Double veined felts
- **Uniform external look throughout the building:** Uniform construction of all applications ensures windows with different DPs maintain the same external look
- **Protection against corrosion and longer life:** Stainless steel components
- **Ease-of-operation and longer life:** Preloaded spring balancers
- **Enhanced energy efficiency:** Insulated glass option available

SPECIFICATIONS:

Maximum Size	Glazing	Nominal Glass	Design Pressure
53 1/8" x 96"	Impact	5/16" Annealed	±60
53 1/8" x 72"	Impact	7/16" Heat Strength	+60/-80
53" x 77"	Impact	7/16" Heat Strength	+80/-100
53 1/2" x 77"*	Impact	1/2" Heat Strength	+120/-150
48" x 72"	Insulated Impact	3/4" IGU - 5/16" HS	±75
53 1/8" x 78"	Insulated Impact	7/8" IGU - 7/16" HS	+80/-100

*Indicated high rise sill

ADDITIONAL SPECIFICATIONS:

Muntin	Flat, Profile
Grid Options	Colonial, Prairie, Perimeter
Frame Depth	3 1/4"
Colors	White, Bronze
Approvals/Certifications	HVHZ, NFRC, Florida Product Approval



DOUBLE HUNG VINYL WINDOW

ENERGY EFFICIENCY & INCREASED CURB APPEAL!

FEATURES & BENEFITS:

- **Nearly impenetrable barrier to air & water penetration:**
Fusion welded 3 ¼" frame & sash provide strength, stability, and rigidity
- **More traditional wood appearance on exterior:**
Unique cove mold design
- **Maximized water runoff, even in driving rain:**
5 degree sloped sill
- **Resists air infiltration:** Deeply pocketed head with weather stripping
- **Better thermal barrier than most other windows:**
.070" walls are a full 12% thicker than most other windows
- **Smooth and maintenance-free operation:** Coil pack balancers
- **Easy sash operation:** Attractive, integral lift rail
- **Easy to clean:** Tilt sash
- **Lifetime warranty on all vinyl frames**
- **Made in the USA Certified®**

SPECIFICATIONS:

Maximum Size	Fin: 48" x 72"
Maximum Size	Flange: 48" x 72"
Design Pressure	+/- 50 PSF
Muntin	Grids Between Glass (GBG) or Simulated Divided Light (SDL)
Grid Options	Colonial, Prairie, Perimeter
Frame Depth	3 ¼"
Frame Style	Fin & Flange
Colors	White, Desert Sand, or Bronze Exterior/White Interior
Approvals/ Certifications	Earthwise, Good Housekeeping Seal, Energy Star, NFRC, Made in the USA Certified®



earthwise
WINDOWS & DOORS



HORIZONTAL ROLLER & HORIZONTAL ROLLER P ALUMINUM IMPACT WINDOW

MAXIMUM STRENGTH, LONGER LIFE, & CORROSION RESISTANT

FEATURES & BENEFITS:

- **Superior Strength and Durability:** 3¼" frame depth
- **Maximize prevention of air and water penetration:** Double veined felts
- **Uniform external look throughout the building:** Uniform construction of all applications ensures windows with different DPs maintain the same external look
- **Protection against corrosion and longer life:** Stainless steel components
- **Ease-of-operation, install and longer life:** Heavy duty adjustable rollers
- **Easy Cleaning:** Removable operating sash



SPECIFICATIONS:

Maximum Size	Glazing	Nominal Glass	Design Pressure
74" x 72" XO or OX	Impact	5/16" Annealed	±60
74" x 72" XO or OX	Insulated Impact	5/8" IGU - 5/16" Ann	±60
72" x 60" XO or OX	Impact	7/16" Heat Strength	±80
74 1/8" x 63" XO or OX	Impact	1/2" Heat Strength	+100/-120
111" x 72" XOX equal	Insulated Impact	5/8" IGU - 5/16" Ann	±60
111" x 72" XOX unequal	Impact	5/16" Ann	±60
120" x 63" XOX*	Impact	1/2" Heat Strength	+100/-120

*Indicates high rise sill

ADDITIONAL SPECIFICATIONS:

Muntin	Flat, Profile
Grid Options	Colonial, Prairie, Perimeter, Other
Frame Depth	3 1/4"
Colors	White, Bronze
Approvals/Certifications	HVHZ, NFRC, Florida Product Approval



HORIZONTAL ROLLER VINYL WINDOW

STRENGTH & STABILITY YOU CAN COUNT ON!

FEATURES & BENEFITS:

- **Nearly impenetrable barrier to air & water penetration:**
Fusion welded 3 ¼" frame & sash provide strength, stability, and rigidity
- **More traditional wood appearance on exterior:**
Unique cove mold design
- **Resists air infiltration:** Deeply pocketed head with weather stripping
- **Better thermal barrier than most other windows:**
.070" walls are a full 12% thicker than most other windows
- **Enhanced leak protection:** No sill screws
- **Lifetime warranty on all vinyl frames**

SPECIFICATIONS:

Maximum Size	71 ½" x 59 ½"
Design Pressure	±50 PSF
Glass	Insulated, Insulated Impact
Muntin	Grids Between Glass (GBG) or Simulated Divided Light (SDL)
Grid Options	Colonial, Prairie, Perimeter
Frame Depth	3 ¼"
Frame Style	Fin & Flange
Colors	White, Desert Sand, or Bronze Exterior/White Interior
Approvals/ Certifications	Earthwise, Good Housekeeping Seal, Energy Star, NFRC, Made in the USA Certified®, Florida Product Approval



earthwise
WINDOWS & DOORS



HVHZ CERTIFIED & MADE IN THE USA!

FEATURES & BENEFITS:

- **Nearly impenetrable barrier to air & water penetration:**
Fusion welded 3 ¼" frame & sash provide strength, stability, and rigidity
- **More traditional wood appearance on exterior:**
Unique cove mold design
- **Resists air infiltration:** Deeply pocketed head with weather stripping
- **Better thermal barrier than most other windows:**
.070" walls are a full 12% thicker than most other windows
- **Enhanced leak protection:** No sill screws
- **Lifetime warranty on all vinyl frames**
- **Made in the USA Certified®**



SPECIFICATIONS:

Maximum Size	Glazing	Frame Option	Design Pressure
111" x 63" XOX equal	Insul. Impact	Fin	+60/-70
		Flange	+65/-85
111" x 63" XOX unequal	Insul. Impact	Fin	+55/-60
		Flange	+50/-65
74" x 63" XO or OX	Insul. Impact	Fin/Fin Only	+70/-85
		Flange	+65/-85

ADDITIONAL SPECIFICATIONS:

Muntin	Grids Between Glass (GBG) or Simulated Divided Light (SDL)
Grid Options	Colonial, Prairie, Perimeter
Frame Depth	3 ¼"
Frame Style	Fin & Flange
Colors	White Desert Sand, or Bronze Exterior/White Interior
Approvals/ Certifications	HVHZ, Earthwise, Good Housekeeping Seal, Energy Star, NFRC, Made in the USA Certified®, Florida Product Approval



HVHZ CERTIFIED, BUDGET FRIENDLY & ENERGY EFFICIENT

FEATURES & BENEFITS:

- **Nearly impenetrable barrier to air & water penetration:**
Fusion welded 3 ¼" frame & sash provide strength, stability, and rigidity
- **More traditional wood appearance on exterior:**
Unique cove mold design
- **Better thermal barrier than most other windows:**
.070" walls are a full 12% thicker than most other windows
- **Cost efficient for retrofits**
- **Lifetime warranty on frames and glass**
- **Made in the USA Certified®**



SPECIFICATIONS:

Maximum Size	53 1/8" X 39"
Design Pressure	+65/-70
Glass	Insulated Impact
Muntin	Grids Between Glass (GBG) or Simulated Divided Light (SDL)
Grid Options	Colonial, Prairie, Perimeter
Frame Depth	3 1/4"
Frame Style	Fin & Flange
Colors	White, Desert Sand, or Bronze Exterior/White Interior
Approvals/ Certifications	HVHZ, Earthwise, Good Housekeeping Seal, Energy Star, NFRC, Made in the USA Certified®, Florida Product Approval



earthwise
WINDOWS & DOORS



VINYL CASEMENT IMPACT WINDOW

SAFETY & BEAUTY IN ONE GREAT PRODUCT!

FEATURES & BENEFITS:

- **Nearly impenetrable barrier to air & water penetration:**
Fusion welded 3 1/4" frame & sash provide strength, stability, and rigidity
- **More traditional wood appearance on exterior:**
Unique cove mold design
- **Maximized water runoff, even in driving rain:**
5 degree sloped sill
- **Resists air infiltration:** Deeply pocketed head with weather stripping
- **Better thermal barrier than most other windows:**
.070" walls are a full 12% thicker than most other windows
- **Enhanced security:** Multi-point lock
- **High end aesthetics:** Egress hinge option
- **Lifetime warranty on all vinyl frames**
- **Limited lifetime warranty:** Truth Hardware with E-Guard



SPECIFICATIONS:

Maximum Size	37" x 76"
Design Pressure	±70 PSF
Glass	Insulated Impact 3/4" IGU- 5/16" Ann
Muntin	Grids Between Glass (GBG) or Simulated Divided Light (SDL)
Grid Options	Colonial, Prairie, Perimeter
Frame Depth	3 1/4"
Frame Style	Fin & Flange
Colors	White, Desert Sand, or Bronze Exterior/White Interior
Approvals/ Certifications	HVHZ, Florida approval number FL15971, Earthwise, Good Housekeeping Seal, Energy Star, NFRC, Made in the USA Certified®



earthwise
WINDOWS & DOORS



**MAXIMUM PROTECTION AGAINST HURRICANE WINDS,
WIND-BORNE DEBRIS, & DRIVING RAIN**



FEATURES & BENEFITS:

- **Nearly impenetrable barrier to air & water penetration:** Fusion welded 3 ¼" frame & sash provide strength, stability, and rigidity
- **More traditional wood appearance on exterior:** Unique cove mold design
- **Maximized water runoff, even in driving rain:** 5 degree sloped sill
- **Better thermal barrier than most other windows:** .070" walls are a full 12% thicker than most other windows
- **Enhanced security:** Multi-point lock
- **High end aesthetics:** Egress hinge option
- **Lifetime warranty:** Frames and glass
- **Limited lifetime warranty:** Truth Hardware with E-Guard. Coastal hardware available
- **Made in the USA Certified®**

SPECIFICATIONS:

Maximum Size	37" x 76"
Design Pressure	±70 PSF
Glass	Insulated Impact ¾" IGU-5/16" Ann
Muntin	Grids Between Glass (GBG) or Simulated Divided Light (SDL)
Grid Options	Colonial, Prairie, Perimeter
Frame Depth	3 ¼"
Colors	White, Desert Sand, or Bronze Exterior/White Interior
Approvals/ Certifications	HVHZ, Earthwise, Good Housekeeping Seal, Energy Star, NFRC, Made in the USA Certified®, Florida Product Approval Number FL15971



FIXED/ARCHITECTURAL VINYL WINDOW

MAKE YOUR VISION A REALITY



FEATURES & BENEFITS:

- **Nearly impenetrable barrier to air & water penetration:** Fusion welded 3 ¼" frame & sash provide strength, stability, and rigidity
- **More traditional wood appearance on exterior:** Unique cove mold design
- **Better thermal barrier than most other windows:** .070" walls are a full 12% thicker than most other windows
- **Lifetime warranty on all vinyl frames**
- **Design flexibility:** Virtually any type of architectural window can be done

SPECIFICATIONS:

Maximum Size	Non-Impact Fin: 71 ½" x 71 ½"
Maximum Size	Non-Impact Flange: 74 ½" x 72"
Maximize Size	Impact: 64" x 84"
Design Pressure	±50 PSF
Glass	Insulated, Insulated Impact
Muntin	Grids Between Glass (GBG) or Simulated Divided Light (SDL)
Grid Options	Colonial, Prairie, Perimeter
Frame Depth	3 ¼"
Colors	White, Desert Sand, or Bronze Exterior/White Interior
Approvals/ Certifications	Earthwise, Good Housekeeping Seal, NFRC, Energy Star, Made in the USA Certified®, Florida State Product Approval



BRING THE OUTSIDE BEAUTY IN, KEEP THE ELEMENTS OUT!



FEATURES & BENEFITS:

- **Nearly impenetrable barrier to air & water penetration:** Fusion welded 3 ¼" frame & sash provide strength, stability, and rigidity
- **More traditional wood appearance on exterior:** Unique cove mold design
- **Better thermal barrier than most other windows:** .070" walls are a full 12% thicker than most other windows
- **Lifetime warranty on frames and glass**
- **Made in the USA Certified®**

SPECIFICATIONS:

Maximum Size	72" x 84"
Design Pressure	±80
Glass	Insulated 1" Glass Pack
Muntin	Grids Between Glass (GBG) or Simulated Divided Light (SDL)
Grid Options	Colonial, Prairie, Perimeter
Frame Depth	3 ¼"
Frame Style	Fin, Flange, Box
Colors	White, Desert Sand, or Bronze Exterior/White Interior
Approvals/ Certifications	HVHZ, Earthwise, Good Housekeeping Seal, Energy Star, NFRC, Made in the USA Certified®, Florida Product Approval



2000 SERIES PICTURE WINDOW IMPACT ALUMINUM

ENJOY THE BEAUTY OF THE OUTSIDE, WITHOUT THE ELEMENTS



FEATURES & BENEFITS:

- **Strong:** Heavy duty aluminum alloy featuring 6063-T6 and heat strengthened glass
- **Uniform external look throughout the building:** Uniform construction of all applications ensures windows with different DPs maintain the same external look
- **Large sizes available:** Tested and approved for XL openings
- **All installation fasteners are concealed** if ordered with Beauty Covers (only available with Picture Windows, not Designers)

SPECIFICATIONS:

Maximum Size	Frame	Design Pressure	Interlayer
44" x 144"	Flange Impact Only	+90/-90	.100 HP

ADDITIONAL SPECIFICATIONS:

Glass Thickness	1/2"
Glass Option	Impact Only
Muntin	Profile/Flat OG/Flat
Grid Options	Colonial, Prairie, Perimeter
Frame Depth	2 5/8"
Frame Style	Flange
Colors	White, Bronze
Approvals/Certifications	HVHZ, NFRC, Florida Product Approval



3000 SERIES PICTURE WINDOW IMPACT ALUMINUM

ENJOY THE BEAUTY OF THE OUTSIDE, WITHOUT THE ELEMENTS



FEATURES & BENEFITS:

- **Strong:** Heavy duty aluminum alloy featuring 6063-T6 and heat strengthened glass
- **Uniform external look throughout the building:** Uniform construction of all applications ensures windows with different DPs maintain the same external look
- **Large sizes available:** Tested and approved for XL openings
- **Finished, high-end look:** Concealed fasteners
- **Allows for multi-configurations**
- **Improved energy efficiency:** Insulated glass option
- **All installation fasteners are concealed**

SPECIFICATIONS:

Maximum Size	Frame	Design Pressure	Interlayer
48" x 120"	Flange Insul. Impact	+95/-100	SGP
48" x 120"	Flange Impact Only	±100	SGP
48" x 120"	Flange	±70	PVB
48" x 54"	Flange	+85/-90	PVB

ADDITIONAL SPECIFICATIONS:

Glass Thickness	7/16" or 1 1/32"
Glass Option	Insulated Impact, Impact Only
Muntin	Grids Between Glass (GBG) or Simulated Divided Light (SDL)
Grid Options	Colonial, Prairie, Perimeter
Frame Depth	3 1/4"
Frame Style	Flange
Colors	White, Bronze
Approvals/Certifications	HVHZ, NFRC, Florida Product Approval



6000 SERIES ALUMINUM SLIDING GLASS DOORS

BUDGET FRIENDLY & OPTION RICH!

FEATURES & BENEFITS:

- Easily adaptable for retro-fit applications
- Added security: Keyed Apollo handle set option
- Corrosion resistant: Stainless steel option

STANDARD ITEMS:

- Mortise Lock with wood handle
- Tandem Rollers
- Secondary Mortise on doors over 80"
- Panel Screens

EXTRA ITEMS:

- Apollo Handle Set: Metal
- Keyed Apollo Handle Set
- Stainless Steel Option

ADDITIONAL INFORMATION:

- When ordering a screen, you MUST order an additional track. I.E. 2 panel with screen will be ordered as a 2D3T system. There is no screen in a 4 track system or on pocket doors.



SPECIFICATIONS:

Glass Thickness	7/16" Impact
Maximum Size	16/0 x 8/0
Muntin	Flat
Grid Options	Colonial, Prairie, Perimeter
Product Rating	Bypass ±80 PSF
Product Rating	Pocket ±45 PSF
Frame Colors	White, Bronze
Approvals/Certifications	HVHZ (for bypass, not pocket), NFRC, Florida Product Approval

FRAME / TRACK SIZES:

	Head	Jamb	Sill
2 Track	3 3/8"	3 5/16"	4 1/16"
3 Track	5"	4 7/8"	6 1/16"
4 Track	6 1/16"	6 1/2"	7 1/16"
Riser for Track Standard			2 1/4"
Riser for Track Add-on	1 1/8"		3 3/8"



FD 8100 SERIES ALUMINUM SLIDING GLASS DOORS

STRENGTH & EASE-OF-USE IN ONE!

FEATURES & BENEFITS:

- **Added Security:** 2-point locking system
- **Enhanced water shedding:** Weep holes in track
- **Smooth Operation:** Stainless steel duel tandem rollers with precision ground bearings

STANDARD ITEMS:

- Dual Mortise Lock w/anti-slam device
- Adjustable dual cams on lock
- Anodized Track Pan w/snap-on cover
- Snap-on jamb covers
- 4" sill on panel

EXTRA ITEMS:

- Secondary Lock (Standard on 84" or taller panels)
- 8" panel sill
- Colonial muntins
- Anodized track cap (only available with O panels)
- 1-piece screen adapter (only available with OXO systems)
- Available in 90 degree or 135 degree configurations
- Configurations: 1 panel to 8 panels with or without pockets



SPECIFICATIONS:

Glass Thickness	¼" tempered, ½" impact, 1" insulated, 1 1/16" insulated impact (must specify standard or reverse system)
Maximum Size	32' x 10', 40' x 9'
Muntin	Flat
Grid Options	Colonial, Prairie, Perimeter
Product Rating	C110
Frame Colors	White, Bronze
Approvals/Certifications	HVHZ, NRFC, Florida Product Approval

FRAME / TRACK SIZES:

	Head	Jamb	Sill
2D2T w/screen	6 3/8"	6 1/4"	7 1/16"
2D2T no screen	5 3/16"	5 1/16"	5 13/16"
2D2T retro	5 3/16"	5 1/16"	5 3/16"
3D3T w/screen	8 7/8"	8 5/8"	9 1/2"
3D3T no screen	7 11/16"	7 1/2"	8 3/8"
4D4T no screen	10 3/16"	9 15/16"	10 13/16"

RISERS FOR TRACK

Standard	1 3/4"
Add-on 1"	2 3/4"
Add-on 2 3/16"	3 15/16"
Riser for Track Add-on 1 1/8"	3 3/8"



623 SERIES VINYL SLIDING GLASS DOORS

THE TRIFECTA IN SLIDING GLASS DOORS: SECURE, STRONG, & EASY TO OPERATE

FEATURES & BENEFITS:

- **Strong, energy efficient and maximum air tightness:**
Multi chambered frame with double weather-stripping
- **Durable:** Aluminum sill cover
- **Added Security:** 2-point locking system and optional keyed handle set

STANDARD ITEMS:

- Fusion Welded, Structurally reinforced sashes
- Dual Mortise Lock w/anti-slam device
- Stainless steel dual tandem rollers with precision ground bearings
- Adjustable dual cams on lock
- Weep holes in track
- Snap on covers to conceal fastener installation
- Anti-lift panel devices

EXTRA ITEMS:

- Easy rolling, no jump panel screen w/adjustable rollers
- Colonial or Prairie muntins between the glass
- Tinted or solar performance glass



SPECIFICATIONS:

Glass Thickness	1" Insulated Impact Glass 1" Insulated Non-Impact Glass
Maximum Size	192" x 96"
Muntin	Grids Between Glass (GBG) or Simulated Divided Light (SDL)
Grid Options	Colonial, Prairie, Perimeter
Product Rating	SD-C50
Frame Colors	White, Desert Sand, or Bronze Exterior/White Interior
Large Missile Impact Level	Level D, Windzone 4
Configurations	OX or XO, OXO, OXXO
Approvals/Certifications	Earthwise, Good Housekeeping Seal, NFRC, Energy Star, Made in the USA Certified®, Florida State Product Approval

FRAME / TRACK SIZES:

	Head	Jamb	Sill
2T w/screen	5 1/8"	5 1/8"	5 1/8"



earthwise
WINDOWS & DOORS



Eastern
ARCHITECTURAL SYSTEMS
ALUMINUM AND VINYL
IMPACT WINDOWS AND DOORS

STRENGTH & ENERGY EFFICIENCY IN ONE GREAT MODEL!
FEATURES & BENEFITS:

- **Strong, energy efficient and maximum air tightness:** Multi chambered frame with double weather-stripping
- **High end look:** Snap on covers conceal fastener installation
- **Added Security:** 2-point locking system and optional keyed handle set

STANDARD ITEMS:

- Fusion welded, structurally reinforced sashes
- Rugged aluminum sill cover
- Dual mortise lock w/anti-slam device
- Stainless steel dual tandem rollers with precision ground bearings
- Adjustable dual cams on lock
- Weep holes in track
- Anti-lift panel devices

EXTRA ITEMS:

- Easy rolling, no jump panel screen w/adjustable rollers
- Colonial or Prairie muntins between the glass
- Tinted or solar performance glass
- Keyed handle set


SPECIFICATIONS:

Glass Thickness	1" Insulated Impact Glass 1" Insulated Non-Impact Glass
Maximum Size	192" x 96"
Design Pressure	±65
Muntin	Grids Between Glass (GBG) or Simulated Divided Light (SDL)
Grid Options	Colonial, Prairie, Perimeter
Frame Colors	White, Desert Sand, or Bronze Exterior/White Interior
Large Missile Impact Level	Level D, Windzone 4
Configurations	OX or XO, OXO, OXXO
Approvals/Certifications	HVHZ, Florida Product Approval, Earthwise, Good Housekeeping Seal, Energy Star, NFRC, Made in the USA Certified®

FRAME / TRACK SIZES:

	Head	Jamb	Sill
2T w/Screen:	5 1/8"	5 1/8"	5 1/8"



5000 SERIES IMPACT ALUMINUM FRENCH DOOR

ELEGANCE, STRENGTH, INTEGRITY & ENERGY EFFICIENCY —
ALL IN ONE PRETTY PACKAGE

FEATURES & BENEFITS:

- **Added security:** Multi-point lock features a double throw bolt design
- **Quiet operation:** Double veined felts
- **Enhanced energy efficiency:** Insulated glass option cuts down on electric consumption

STANDARD ITEMS:

- Heavy walled construction
- High-quality locking hardware by Interlock
- High mil rubber weather stripping used for a tighter seal
- ADA sill for low clearance

OPTIONAL ITEMS:

- Stainless Steel Components
- 1 ½" Sill Riser (for higher design pressure)
- Insulated Impact Glass
- Impact Glass Only



SPECIFICATIONS:

Maximum Size	Double Doors: 75" x 97 1/16" overall frame Single Doors: 39" X 97 1/16" overall frame
Glass Thickness	7/16" Impact, 1" overall Impact Insulated
Design Pressure	3' x 8' w/ sill riser: ± 100 6' x 8' w/ sill riser: ± 75
Muntin	Flat or Grids on insulated units
Grid Options	Colonial, Prairie, Perimeter
Frame Depth	4 3/4"
Frame Colors	White, Bronze
Large Missile Impact Level	Level D, Windzone 4
Approvals/Certifications	HVHZ, NFRC, Florida Product Approvals



650 SERIES PATIO DOOR SYSTEM

VINYL MULTI-TRACK POCKETING DOOR - PERFECT BALANCE OF FORM & FUNCTION

FEATURES & BENEFITS:

- **Smooth Operation:** Panels stack neatly to create an ultra-wide opening with clean sight lines
- Can be installed in traditional and pocket installations
- New construction and replacement
- Up to 8 panels wide
- Heavy aluminum interlocks with vinyl covers

STANDARD ITEMS:

- Stainless Steel Tandem rollers
- Dual Mortise Lock w/anti-slam device
- Adjustable dual cams on locks
- Anodized Track cover
- Sunshield - a proprietary high-performance vinyl compound
- European handle design

EXTRA ITEMS:

- Colonial muntins
- Anodized track cap (only available with O panels)
- 1-piece screen adapter (only available with OXO systems)
- Configurations: 2,3,4 multi-track configuration with pocket capabilities
- European handle available in white or brushed nickel
- Single and double pocket configuration

SPECIFICATIONS:

Glass Thickness	1 1/16" insulated impact 1" insulated
Maximum Size	32' x 8'
Muntin	Flat, GBG & SDL available
Grid Options	Colonial, Prairie, Perimeter
Product Rating	DP +/-80
Frame Colors	White
Approvals/Certifications	HVHZ, NRFC, Florida Product Approval, ASTM



FRAME / TRACK SIZES:

Track Width	Sill
2D2T no screen	5 1/2"
2D2T w/screen	7 1/8"
3D3T no screen	7 11/16"
3D3T w/screen	9 5/16"
4D4T no screen	9 15/16"
4D4T w/screen	11 9/16"

RISERS FOR TRACK

60 DP	3 1/2"
80 DP	4"



7000 SERIES ALUMINUM SLIDING GLASS DOORS

STRENGTH & EASE-OF-USE IN ONE!

FEATURES & BENEFITS:

- **Added Security:** 2-point locking system
- **Enhanced water shedding:** Weep holes in track
- **Smooth Operation:** Stainless steel housing with nylon roller
- **Reversible interlocks**

STANDARD ITEMS:

- Dual Mortise Lock w/anti-slam device
- Adjustable dual cams on lock
- Anodized Track Pan w/snap-on cover
- 3 3/4" sill on panel

EXTRA ITEMS:

- Secondary Lock
- Stainless Steel Roller
- Colonial muntins
- Anodized track cap (only available with O panels)
- Configurations: 1 panel to 8 panels with or without pockets



SPECIFICATIONS:

Glass Thickness	7/16" impact, 1" insulated impact (must specify standard or reverse system)
Maximum Size	32' x 8'
Muntin	Flat
Grid Options	Colonial, Prairie, Perimeter
Product Rating	60+/-60
Frame Colors	White, Bronze
Approvals/Certifications	HVHZ, NRFC, Florida Product Approval

FRAME / TRACK SIZES:

	Head	Jamb	Sill
2D2T no screen	4 1/8"	3 15/16"	4 1/4"
2D2T w/screen	5 3/8"	5 1/4"	5 1/2"
3D3T no screen	6 1/8"	6"	6 1/4"
3D3T w/screen	7 7/16"	7 1/4"	7 9/16"
4D4T no screen	8 3/16"	8"	8 1/4"
4D4T w/screen	9 1/2"	9 5/16"	9 9/16"

RISERS FOR TRACK

Standard	1 15/16"
Add-on 1"	3"
Add-on 2"	4"

