

3000 SERIES PICTURE WINDOW IMPACT ALUMINUM

ENJOY THE BEAUTY OF THE OUTSIDE, WITHOUT THE ELEMENTS



FEATURES & BENEFITS:

- **Strong:** Heavy duty aluminum alloy featuring 6063-T6 and heat strengthened glass
- **Uniform external look throughout the building:** Uniform construction of all applications ensures windows with different DPs maintain the same external look
- **Large sizes available:** Tested and approved for XL openings
- **Finished, high-end look:** Concealed fasteners
- **Allows for multi-configurations**
- **Improved energy efficiency:** Insulated glass option
- **All installation fasteners are concealed**

SPECIFICATIONS:

Maximum Size	Frame	Design Pressure	Interlayer
48" x 120"	Flange Insul. Impact	+95/-100	SGP
48" x 120"	Flange Impact Only	±100	SGP
48" x 120"	Flange	±70	PVB
48" x 54"	Flange	+85/-90	PVB

ADDITIONAL SPECIFICATIONS:

Glass Thickness	7/16" or 1 1/32"
Glass Option	Insulated Impact, Impact Only
Muntin	Grids Between Glass (GBG) or Simulated Divided Light (SDL)
Grid Options	Colonial, Prairie, Perimeter
Frame Depth	3 1/4"
Frame Style	Flange
Colors	White, Bronze
Approvals/Certifications	HVHZ, NFRC, Florida Product Approval

