

SINGLE HUNG IMPACT ALUMINUM WINDOW

MAXIMIZE PROTECTION AGAINST WATER AND WIND-BORNE DEBRIS — AT A GREAT VALUE



FEATURES & BENEFITS:

- **Superior Strength and Durability:**
3¼" frame depth
- **Maximize prevention of air and water penetration:** Double veined felts
- **Uniform external look throughout the building:** Uniform construction of all applications ensures windows with different DPs maintain the same external look
- **Protection against corrosion and longer life:** Stainless steel components
- **Ease-of-operation and longer life:** Preloaded spring balancers
- **Enhanced energy efficiency:** Insulated glass option available

SPECIFICATIONS:

Maximum Size	Glazing	Nominal Glass	Design Pressure
53 1/8" x 96"	Impact	5/16" Annealed	±60
53 1/8" x 72"	Impact	7/16" Heat Strength	+60/-80
53" x 77"	Impact	7/16" Heat Strength	+80/-100
53 1/2" x 77"*	Impact	1/2" Heat Strength	+120/-150
48" x 72"	Insulated Impact	3/4" IGU - 5/16" HS	±75
53 1/8" x 78"	Insulated Impact	7/8" IGU - 7/16" HS	+80/-100

*Indicated high rise sill

ADDITIONAL SPECIFICATIONS:

Muntin	Flat, Profile
Grid Options	Colonial, Prairie, Perimeter
Frame Depth	3 1/4"
Colors	White, Bronze
Approvals/Certifications	HVHZ, NFRC, Florida Product Approval

