

## **Screen Cleaners**



ELECTRIC AND PNEUMATIC SCREEN CLEANER DATA								
Model	Service Requirements	Shipping Weight	Motor Size/ Speed	Max. Discharge Pressure	Max. Flow	Wand Type	Tank Size	Dimensions
RS-ESC-NT Electric Screen Cleaner, No Tank	480V/60HZ/3Ph/10A Breaker; Fluid Inlet Hose with 3/8" crow's foot	120 lbs	2 HP/1800RPM (electric)	700 PSI	1.5 GPM	Single Wand, 48" with 5.0 Tip	N/A	30" x 22" x 33"
RS-ESC-WT Electric Screen Cleaner, With Tank	480V/60HZ/3Ph/10A Breaker	150 lbs	2 HP/1800RPM (electric)	700 PSI	1.5 GPM	Single Wand, 48" with 5.0 Tip	27 Gallons	30" x 22" x 33"
RS-ESC-WT-OS Offshore Electric Screen Cleaner, With Tank	480V/60HZ/3Ph/10A Breaker	200 lbs	2 HP/1800RPM (electric)	700 PSI	1.5 GPM	Single Wand, 48" with 5.0 Tip	27 Gallons	31.46" x 29.44" x 50"
RS-PSC-NT Pneumatic Screen Cleaner, No Tank	Rig Air Hose with 3/8" crow's foot; Fluid Inlet Hose with 3/8" crow's foot	80 lbs	4 HP/3000RPM (pneumatic)	700 PSI	1.5 GPM	Single Wand, 48" with 5.0 Tip	N/A	22.25" x 24.14" x 20.50"
RS-PSC-WT Pneumatic Screen Cleaner, With Tank	Rig Air Hose with 3/8" crow's foot	110 lbs	4 HP/3000RPM (pneumatic)	700 PSI	1.5 GPM	Single Wand, 48" with 5.0 Tip	27 Gallons	30" x 22" x 33"
RS-PSC-WT-OS Offshore Pneumatic Screen Cleaner, With Tank	Rig Air Hose with 3/8" crow's foot	160 lbs	4 HP/3000RPM (pneumatic)	700 PSI	1.5 GPM	Single Wand, 48" with 5.0 Tip	27 Gallons	22.25" x 24.14" x 20.50"

