

SNOW GUARD BRACKET ATTACHED TO BASE PLATE WITH S.S. NUTS AND NEOPRENE WASHERS



FTR MEMBRANE TARGET FLASHING CENTERED OVER BASE PLATE, HOT AIR WELD CONTINUOUS (MIN. 2" WIDE WELD)

SNOW GUARD BASE PLATE, FASTEN INTO WOOD BLOCKING WITH COUNTERSUNK FASTENERS

APPLY FTR 101 SEALANT AROUND STUDS OF BASE PLATE PRIOR TO INSTALLING TARGET FLASHING

FTR REINFORCED MEMBRANE PROTECTION LAYER AT BASE PLATE LOCATION, HOT AIR WELD CONTINUOUS (MIN. 2" WIDE WELD)

FTR OR FTR-FB MEMBRANE (PER SPECIFICATION)

WOOD BLOCKING FOR SNOW GUARD BASE PLATE ATTACHMENT, SECURELY FASTENED TO ROOF DECK

INSULATION ATTACHED PER SPECIFICATION REQUIREMENTS

ROOF DECK



GENERAL REFERENCE:
 "FTR GS 02/13"
 APPLICABLE SYSTEMS:
 "FTR AD 02/13"
 "FTR SMRP 02/13"

SNOW GUARD "NEW CONSTRUCTION"		
REVISES DETAIL	ISSUE DATE	DRAWING NUMBER
ALL PREVIOUS	02-10-14	FTR-SGNC