

Product Reference: FTR Value_A Insulation

Energy & Atmosphere - Minimum Energy Performance: Prerequisite 2

Polyisocyanurate roof insulation is thermally efficient and can contribute toward exceeding ASHRAE 90.1-1999 as well as local energy codes.

Energy & Atmosphere - Optimize Energy Performance: Credit 1

Polyisocyanurate roof insulation offers the highest thermal resistance per inch of roof insulation material and can contribute to achieving economically/optimized energy performance

MR Credit 4.1; 4.2 – Recycled Content	Percent by Weight (%)	Post-consumer Weight (%)	Pre-consumer Weight (%)
Thickness (in inches): 1.0"	43	24.5	18.5
1.1"	40	22.8	17.2
1.2"	38	21.7	16.3
1.3"	36	20.5	15.5
1.4"	35	20.0	15.0
1.5"	33	18.8	14.2
1.6"	32	18.2	13.8
1.7"	30	17.1	12.9
1.8"	29	16.5	12.5
1.9"	28	16.0	12.0
2.0"	27	15.4	11.6
2.5"	23	13.1	09.9

MR Credit 5.1; 5.2 – Regional Materials

Primary Manufacturing (City, State, Zip Code):

(Extraction: N/A)

Location

Camp Hill, PA 17011

LaGrange, Georgia 3024

Diboll, Texas 75941

East Moline, Illinois 61244

Northglenn, Colorado 80233

Phoenix, Arizona 85043