

Product Reference: FTR Value_H Insulation

Energy & Atmosphere - Minimum Energy Performance: Prerequisite 2

Polyisocyanurate roof insulation is thermally efficient and can contribute toward exceeding ASHRAE 90.1-1999 as well as local energy codes.

Energy & Atmosphere - Optimize Energy Performance: Credit 1

Polyisocyanurate roof insulation offers the highest thermal resistance per inch of roof insulation material and can contribute to achieving economically/optimized energy performance

MR Credit 4.1; 4.2 – Recycled Content	Percent by Weight (%)	Post-consumer Weight (%)	Pre-consumer Weight (%)
Thickness (in inches): 1.0"	37.8	27.8	10.0
1.1"	36.2	26.2	10.0
1.2"	34.5	24.6	9.9
1.3"	33.2	23.3	9.9
1.4"	31.9	22.1	9.8
1.5"	30.8	21.0	9.8
1.6"	29.7	20.0	9.7
1.7"	28.8	19.1	9.7
1.8"	28.0	18.3	9.7
1.9"	27.2	17.5	9.7
2.0"	26.5	16.9	9.6

MR Credit 5.1; 5.2 – Regional Materials

Primary Manufacturing (City, State, Zip Code):

Location

Kinston, New York 12401

Terrell, Texas 75160

Chicago, Illinois 60131

Lake City, Florida 32025

Toole, Utah 84074

Smithfield, Pennsylvania 15478

(Extraction: N/A)