

FiberTite Technical Bulletin #2018.004

Seaman Corporation • 1000 Venture Blvd. • Wooster, OH 44691 www.fibertite.com

Issue Date: April 2nd, 2018

Issued By: FiberTite Technical Services

Re: New FiberTite® Drain Flashing Construction Details

New FiberTite Drain Flashing Construction Details

2018.004 - Page One of One:

FiberTite Roofing Systems has added three (3) options for Drain Flashing Details to include the use of FiberTite Roofing Membranes.

The new Drain Details are:

- 1. FTR-DD3 Typical Drain Flashing w/ Fleeceback Membrane
- 2. FTR-DD4 Typical Reinforced Drain Flashing
- 3. FTR-DD5 Minimal Slope Drain Flashing

Drain Detail Drawings FTR-DD3 and FTR-DD4 illustrate typical sumped drains. The FiberTite membrane should be cut to fit the sump area, *and not stretched in place*.

Drain Detail Drawing FTR-DD5 illustrates a typical non-sumped drain, and does not utilize an individual drain flashing target. As shown on the Detail Drawing, *fasteners are required around the drain area*.

The use of FiberTite 60-mil non-reinforced flashing membrane remains a standard option for drain detail flashing.

These three (3) new Drain Details Drawings can be found at FiberTite.com, in the *Construction Details* section of the *Document Library*. The drawings are found under *Penetrations*.

For questions or additional information, please contact FiberTite Technical Services at: 800.927.8578.

FiberTite $^{\text{@}}$ is a Registered Trademark of Seaman Corporation